



Welcome

Managed integrations



API Version 2025-03-03

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Managed integrations: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome **1**

Actions **2**

CreateAccountAssociation 5

Request Syntax 5

URI Request Parameters 5

Request Body 5

Response Syntax 7

Response Elements 7

Errors 8

See Also 9

CreateCloudConnector 11

Request Syntax 11

URI Request Parameters 11

Request Body 11

Response Syntax 13

Response Elements 13

Errors 13

See Also 14

CreateConnectorDestination 15

Request Syntax 15

URI Request Parameters 16

Request Body 16

Response Syntax 18

Response Elements 18

Errors 18

See Also 19

CreateCredentialLocker 21

Request Syntax 21

URI Request Parameters 21

Request Body 21

Response Syntax 22

Response Elements 22

Errors 23

See Also 24

CreateDestination	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	28
Response Elements	28
Errors	29
See Also	30
CreateEventLogConfiguration	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	32
Response Elements	32
Errors	33
See Also	34
CreateManagedThing	35
Request Syntax	35
URI Request Parameters	36
Request Body	36
Response Syntax	41
Response Elements	41
Errors	42
See Also	43
CreateNotificationConfiguration	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	46
Response Elements	47
Errors	47
See Also	48
CreateOtaTask	49
Request Syntax	49
URI Request Parameters	50
Request Body	50

Response Syntax	52
Response Elements	53
Errors	54
See Also	55
CreateOtaTaskConfiguration	56
Request Syntax	56
URI Request Parameters	57
Request Body	57
Response Syntax	58
Response Elements	58
Errors	58
See Also	59
CreateProvisioningProfile	61
Request Syntax	61
URI Request Parameters	61
Request Body	61
Response Syntax	63
Response Elements	63
Errors	65
See Also	66
DeleteAccountAssociation	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	67
Response Elements	67
Errors	68
See Also	68
DeleteCloudConnector	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	70
Response Elements	70
Errors	70
See Also	71

DeleteConnectorDestination	73
Request Syntax	73
URI Request Parameters	73
Request Body	73
Response Syntax	73
Response Elements	73
Errors	74
See Also	74
DeleteCredentialLocker	76
Request Syntax	76
URI Request Parameters	76
Request Body	76
Response Syntax	76
Response Elements	76
Errors	77
See Also	77
DeleteDestination	79
Request Syntax	79
URI Request Parameters	79
Request Body	79
Response Syntax	79
Response Elements	79
Errors	79
See Also	80
DeleteEventLogConfiguration	82
Request Syntax	82
URI Request Parameters	82
Request Body	82
Response Syntax	82
Response Elements	82
Errors	82
See Also	83
DeleteManagedThing	85
Request Syntax	85
URI Request Parameters	85
Request Body	85

Response Syntax	85
Response Elements	85
Errors	86
See Also	87
DeleteNotificationConfiguration	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	88
Errors	88
See Also	89
DeleteOtaTask	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	91
Response Elements	91
Errors	91
See Also	92
DeleteOtaTaskConfiguration	94
Request Syntax	94
URI Request Parameters	94
Request Body	94
Response Syntax	94
Response Elements	94
Errors	94
See Also	95
DeleteProvisioningProfile	97
Request Syntax	97
URI Request Parameters	97
Request Body	97
Response Syntax	97
Response Elements	97
Errors	97
See Also	99

DeregisterAccountAssociation	100
Request Syntax	100
URI Request Parameters	100
Request Body	100
Response Syntax	101
Response Elements	101
Errors	101
See Also	102
GetAccountAssociation	103
Request Syntax	103
URI Request Parameters	103
Request Body	103
Response Syntax	103
Response Elements	104
Errors	106
See Also	107
GetCloudConnector	108
Request Syntax	108
URI Request Parameters	108
Request Body	108
Response Syntax	108
Response Elements	109
Errors	110
See Also	111
GetConnectorDestination	112
Request Syntax	112
URI Request Parameters	112
Request Body	112
Response Syntax	112
Response Elements	113
Errors	115
See Also	116
GetCredentialLocker	117
Request Syntax	117
URI Request Parameters	117
Request Body	117

Response Syntax	117
Response Elements	118
Errors	119
See Also	120
GetCustomEndpoint	121
Request Syntax	121
URI Request Parameters	121
Request Body	121
Response Syntax	121
Response Elements	121
Errors	122
See Also	123
GetDefaultEncryptionConfiguration	124
Request Syntax	124
URI Request Parameters	124
Request Body	124
Response Syntax	124
Response Elements	124
Errors	125
See Also	126
GetDestination	128
Request Syntax	128
URI Request Parameters	128
Request Body	128
Response Syntax	128
Response Elements	129
Errors	130
See Also	131
GetDeviceDiscovery	133
Request Syntax	133
URI Request Parameters	133
Request Body	133
Response Syntax	133
Response Elements	134
Errors	136
See Also	137

GetEventLogConfiguration	138
Request Syntax	138
URI Request Parameters	138
Request Body	138
Response Syntax	138
Response Elements	138
Errors	139
See Also	140
GetHubConfiguration	142
Request Syntax	142
URI Request Parameters	142
Request Body	142
Response Syntax	142
Response Elements	142
Errors	143
See Also	144
GetManagedThing	145
Request Syntax	145
URI Request Parameters	145
Request Body	145
Response Syntax	145
Response Elements	146
Errors	152
See Also	153
GetManagedThingCapabilities	155
Request Syntax	155
URI Request Parameters	155
Request Body	155
Response Syntax	155
Response Elements	156
Errors	157
See Also	158
GetManagedThingCertificate	159
Request Syntax	159
URI Request Parameters	159
Request Body	159

Response Syntax	159
Response Elements	159
Errors	160
See Also	161
GetManagedThingConnectivityData	162
Request Syntax	162
URI Request Parameters	162
Request Body	162
Response Syntax	162
Response Elements	162
Errors	163
See Also	164
GetManagedThingMetaData	166
Request Syntax	166
URI Request Parameters	166
Request Body	166
Response Syntax	166
Response Elements	167
Errors	167
See Also	168
GetManagedThingState	170
Request Syntax	170
URI Request Parameters	170
Request Body	170
Response Syntax	170
Response Elements	171
Errors	171
See Also	172
GetNotificationConfiguration	173
Request Syntax	173
URI Request Parameters	173
Request Body	173
Response Syntax	173
Response Elements	174
Errors	175
See Also	176

GetOtaTask	177
Request Syntax	177
URI Request Parameters	177
Request Body	177
Response Syntax	177
Response Elements	178
Errors	181
See Also	182
GetOtaTaskConfiguration	184
Request Syntax	184
URI Request Parameters	184
Request Body	184
Response Syntax	184
Response Elements	185
Errors	186
See Also	187
GetProvisioningProfile	188
Request Syntax	188
URI Request Parameters	188
Request Body	188
Response Syntax	188
Response Elements	189
Errors	190
See Also	191
GetRuntimeLogConfiguration	193
Request Syntax	193
URI Request Parameters	193
Request Body	193
Response Syntax	193
Response Elements	194
Errors	194
See Also	195
GetSchemaVersion	196
Request Syntax	196
URI Request Parameters	196
Request Body	196

Response Syntax	196
Response Elements	197
Errors	198
See Also	199
ListAccountAssociations	201
Request Syntax	201
URI Request Parameters	201
Request Body	201
Response Syntax	201
Response Elements	202
Errors	202
See Also	203
ListCloudConnectors	205
Request Syntax	205
URI Request Parameters	205
Request Body	205
Response Syntax	206
Response Elements	206
Errors	207
See Also	207
ListConnectorDestinations	209
Request Syntax	209
URI Request Parameters	209
Request Body	209
Response Syntax	209
Response Elements	210
Errors	210
See Also	211
ListCredentialLockers	212
Request Syntax	212
URI Request Parameters	212
Request Body	212
Response Syntax	212
Response Elements	213
Errors	213
See Also	214

ListDestinations	215
Request Syntax	215
URI Request Parameters	215
Request Body	215
Response Syntax	215
Response Elements	216
Errors	216
See Also	217
ListDeviceDiscoveries	218
Request Syntax	218
URI Request Parameters	218
Request Body	218
Response Syntax	219
Response Elements	219
Errors	219
See Also	220
ListDiscoveredDevices	222
Request Syntax	222
URI Request Parameters	222
Request Body	222
Response Syntax	223
Response Elements	223
Errors	224
See Also	225
ListEventLogConfigurations	226
Request Syntax	226
URI Request Parameters	226
Request Body	226
Response Syntax	226
Response Elements	227
Errors	227
See Also	228
ListManagedThingAccountAssociations	229
Request Syntax	229
URI Request Parameters	229
Request Body	230

Response Syntax	230
Response Elements	230
Errors	231
See Also	231
ListManagedThings	233
Request Syntax	233
URI Request Parameters	233
Request Body	235
Response Syntax	235
Response Elements	236
Errors	236
See Also	237
ListManagedThingSchemas	238
Request Syntax	238
URI Request Parameters	238
Request Body	239
Response Syntax	239
Response Elements	239
Errors	240
See Also	241
ListNotificationConfigurations	242
Request Syntax	242
URI Request Parameters	242
Request Body	242
Response Syntax	242
Response Elements	243
Errors	243
See Also	244
ListOtaTaskConfigurations	245
Request Syntax	245
URI Request Parameters	245
Request Body	245
Response Syntax	245
Response Elements	246
Errors	246
See Also	247

ListOtaTaskExecutions	248
Request Syntax	248
URI Request Parameters	248
Request Body	248
Response Syntax	248
Response Elements	249
Errors	249
See Also	250
ListOtaTasks	252
Request Syntax	252
URI Request Parameters	252
Request Body	252
Response Syntax	252
Response Elements	253
Errors	253
See Also	254
ListProvisioningProfiles	255
Request Syntax	255
URI Request Parameters	255
Request Body	255
Response Syntax	255
Response Elements	256
Errors	256
See Also	257
ListSchemaVersions	259
Request Syntax	259
URI Request Parameters	259
Request Body	260
Response Syntax	260
Response Elements	261
Errors	261
See Also	262
ListTagsForResource	263
Request Syntax	263
URI Request Parameters	263
Request Body	263

Response Syntax	263
Response Elements	264
Errors	264
See Also	265
PutDefaultEncryptionConfiguration	266
Request Syntax	266
URI Request Parameters	266
Request Body	266
Response Syntax	267
Response Elements	267
Errors	268
See Also	269
PutHubConfiguration	270
Request Syntax	270
URI Request Parameters	270
Request Body	270
Response Syntax	270
Response Elements	271
Errors	271
See Also	272
PutRuntimeLogConfiguration	273
Request Syntax	273
URI Request Parameters	273
Request Body	273
Response Syntax	274
Response Elements	274
Errors	274
See Also	275
RegisterAccountAssociation	276
Request Syntax	276
URI Request Parameters	276
Request Body	276
Response Syntax	277
Response Elements	277
Errors	278
See Also	279

RegisterCustomEndpoint	280
Request Syntax	280
URI Request Parameters	280
Request Body	280
Response Syntax	280
Response Elements	280
Errors	281
See Also	282
ResetRuntimeLogConfiguration	283
Request Syntax	283
URI Request Parameters	283
Request Body	283
Response Syntax	283
Response Elements	283
Errors	283
See Also	284
SendConnectorEvent	286
Request Syntax	286
URI Request Parameters	288
Request Body	288
Response Syntax	291
Response Elements	291
Errors	292
See Also	292
SendManagedThingCommand	294
Request Syntax	294
URI Request Parameters	294
Request Body	295
Response Syntax	296
Response Elements	296
Errors	296
See Also	297
StartAccountAssociationRefresh	299
Request Syntax	299
URI Request Parameters	299
Request Body	299

Response Syntax	299
Response Elements	299
Errors	300
See Also	301
StartDeviceDiscovery	302
Request Syntax	302
URI Request Parameters	302
Request Body	302
Response Syntax	306
Response Elements	307
Errors	307
See Also	308
TagResource	310
Request Syntax	310
URI Request Parameters	310
Request Body	310
Response Syntax	311
Response Elements	311
Errors	311
See Also	312
UntagResource	313
Request Syntax	313
URI Request Parameters	313
Request Body	313
Response Syntax	313
Response Elements	314
Errors	314
See Also	314
UpdateAccountAssociation	316
Request Syntax	316
URI Request Parameters	316
Request Body	316
Response Syntax	317
Response Elements	317
Errors	317
See Also	318

UpdateCloudConnector	320
Request Syntax	320
URI Request Parameters	320
Request Body	320
Response Syntax	321
Response Elements	321
Errors	321
See Also	322
UpdateConnectorDestination	323
Request Syntax	323
URI Request Parameters	324
Request Body	324
Response Syntax	325
Response Elements	325
Errors	325
See Also	326
UpdateDestination	328
Request Syntax	328
URI Request Parameters	328
Request Body	328
Response Syntax	329
Response Elements	329
Errors	330
See Also	330
UpdateEventLogConfiguration	332
Request Syntax	332
URI Request Parameters	332
Request Body	332
Response Syntax	333
Response Elements	333
Errors	333
See Also	334
UpdateManagedThing	335
Request Syntax	335
URI Request Parameters	336
Request Body	336

Response Syntax	340
Response Elements	340
Errors	340
See Also	341
UpdateNotificationConfiguration	342
Request Syntax	342
URI Request Parameters	342
Request Body	342
Response Syntax	343
Response Elements	343
Errors	343
See Also	344
UpdateOtaTask	345
Request Syntax	345
URI Request Parameters	345
Request Body	345
Response Syntax	346
Response Elements	346
Errors	346
See Also	347
Data Types	348
AbortConfigCriteria	351
Contents	351
See Also	352
AccountAssociationItem	353
Contents	353
See Also	355
AuthConfig	356
Contents	356
See Also	356
AuthConfigUpdate	357
Contents	357
See Also	357
AuthMaterial	358
Contents	358
See Also	358

CapabilityAction	359
Contents	359
See Also	360
CapabilityReport	361
Contents	361
See Also	361
CapabilityReportCapability	363
Contents	363
See Also	364
CapabilityReportEndpoint	366
Contents	366
See Also	367
CapabilitySchemaltem	368
Contents	368
See Also	369
CommandCapability	370
Contents	370
See Also	371
CommandEndpoint	372
Contents	372
See Also	372
ConfigurationError	373
Contents	373
See Also	373
ConfigurationStatus	374
Contents	374
See Also	374
ConnectorDestinationSummary	375
Contents	375
See Also	376
ConnectorItem	377
Contents	377
See Also	378
CredentialLockerSummary	379
Contents	379
See Also	380

DestinationSummary	381
Contents	381
See Also	382
Device	383
Contents	383
See Also	384
DeviceDiscoverySummary	385
Contents	385
See Also	385
DiscoveredDeviceSummary	387
Contents	387
See Also	389
EndpointConfig	390
Contents	390
See Also	390
EventLogConfigurationSummary	391
Contents	391
See Also	392
ExponentialRolloutRate	393
Contents	393
See Also	393
GeneralAuthorizationName	395
Contents	395
See Also	395
GeneralAuthorizationUpdate	396
Contents	396
See Also	396
LambdaConfig	397
Contents	397
See Also	397
ManagedThingAssociation	398
Contents	398
See Also	399
ManagedThingSchemaListItem	400
Contents	400
See Also	400

ManagedThingSummary	402
Contents	402
See Also	407
MatterCapabilityReport	408
Contents	408
See Also	408
MatterCapabilityReportAttribute	410
Contents	410
See Also	410
MatterCapabilityReportCluster	412
Contents	412
See Also	414
MatterCapabilityReportEndpoint	416
Contents	416
See Also	417
MatterCluster	419
Contents	419
See Also	420
MatterEndpoint	421
Contents	421
See Also	421
NotificationConfigurationSummary	422
Contents	422
See Also	422
OAuthConfig	423
Contents	423
See Also	424
OAuthUpdate	425
Contents	425
See Also	425
OtaTaskAbortConfig	426
Contents	426
See Also	426
OtaTaskConfigurationSummary	427
Contents	427
See Also	427

OtaTaskExecutionRetryConfig	429
Contents	429
See Also	429
OtaTaskExecutionRolloutConfig	430
Contents	430
See Also	430
OtaTaskExecutionSummaries	431
Contents	431
See Also	431
OtaTaskExecutionSummary	432
Contents	432
See Also	433
OtaTaskSchedulingConfig	434
Contents	434
See Also	434
OtaTaskSummary	436
Contents	436
See Also	437
OtaTaskTimeoutConfig	438
Contents	438
See Also	438
ProactiveRefreshTokenRenewal	439
Contents	439
See Also	439
ProvisioningProfileSummary	440
Contents	440
See Also	441
PushConfig	442
Contents	442
See Also	442
RetryConfigCriteria	443
Contents	443
See Also	443
RolloutRateIncreaseCriteria	444
Contents	444
See Also	444

RuntimeLogConfigurations	445
Contents	445
See Also	446
ScheduleMaintenanceWindow	447
Contents	447
See Also	447
SchemaVersionListItem	448
Contents	448
See Also	449
SecretsManager	450
Contents	450
See Also	450
StateCapability	451
Contents	451
See Also	452
StateEndpoint	453
Contents	453
See Also	453
TaskProcessingDetails	454
Contents	454
See Also	455
WiFiSimpleSetupConfiguration	456
Contents	456
See Also	456
Common Parameters	458
Common Error Types	461

Welcome

Managed integrations is a feature of AWS IoT Device Management that enables developers to quickly build innovative IoT solutions. Customers can use managed integrations to automate device setup workflows and support interoperability across many devices, regardless of device vendor or connectivity protocol. This allows developers to use a single user-interface to control, manage, and operate a range of devices.

This document was last published on October 30, 2026.

Actions

The following actions are supported:

- [CreateAccountAssociation](#)
- [CreateCloudConnector](#)
- [CreateConnectorDestination](#)
- [CreateCredentialLocker](#)
- [CreateDestination](#)
- [CreateEventLogConfiguration](#)
- [CreateManagedThing](#)
- [CreateNotificationConfiguration](#)
- [CreateOtaTask](#)
- [CreateOtaTaskConfiguration](#)
- [CreateProvisioningProfile](#)
- [DeleteAccountAssociation](#)
- [DeleteCloudConnector](#)
- [DeleteConnectorDestination](#)
- [DeleteCredentialLocker](#)
- [DeleteDestination](#)
- [DeleteEventLogConfiguration](#)
- [DeleteManagedThing](#)
- [DeleteNotificationConfiguration](#)
- [DeleteOtaTask](#)
- [DeleteOtaTaskConfiguration](#)
- [DeleteProvisioningProfile](#)
- [DeregisterAccountAssociation](#)
- [GetAccountAssociation](#)
- [GetCloudConnector](#)
- [GetConnectorDestination](#)
- [GetCredentialLocker](#)

- [GetCustomEndpoint](#)
- [GetDefaultEncryptionConfiguration](#)
- [GetDestination](#)
- [GetDeviceDiscovery](#)
- [GetEventLogConfiguration](#)
- [GetHubConfiguration](#)
- [GetManagedThing](#)
- [GetManagedThingCapabilities](#)
- [GetManagedThingCertificate](#)
- [GetManagedThingConnectivityData](#)
- [GetManagedThingMetaData](#)
- [GetManagedThingState](#)
- [GetNotificationConfiguration](#)
- [GetOtaTask](#)
- [GetOtaTaskConfiguration](#)
- [GetProvisioningProfile](#)
- [GetRuntimeLogConfiguration](#)
- [GetSchemaVersion](#)
- [ListAccountAssociations](#)
- [ListCloudConnectors](#)
- [ListConnectorDestinations](#)
- [ListCredentialLockers](#)
- [ListDestinations](#)
- [ListDeviceDiscoveries](#)
- [ListDiscoveredDevices](#)
- [ListEventLogConfigurations](#)
- [ListManagedThingAccountAssociations](#)
- [ListManagedThings](#)
- [ListManagedThingSchemas](#)
- [ListNotificationConfigurations](#)

- [ListOtaTaskConfigurations](#)
- [ListOtaTaskExecutions](#)
- [ListOtaTasks](#)
- [ListProvisioningProfiles](#)
- [ListSchemaVersions](#)
- [ListTagsForResource](#)
- [PutDefaultEncryptionConfiguration](#)
- [PutHubConfiguration](#)
- [PutRuntimeLogConfiguration](#)
- [RegisterAccountAssociation](#)
- [RegisterCustomEndpoint](#)
- [ResetRuntimeLogConfiguration](#)
- [SendConnectorEvent](#)
- [SendManagedThingCommand](#)
- [StartAccountAssociationRefresh](#)
- [StartDeviceDiscovery](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccountAssociation](#)
- [UpdateCloudConnector](#)
- [UpdateConnectorDestination](#)
- [UpdateDestination](#)
- [UpdateEventLogConfiguration](#)
- [UpdateManagedThing](#)
- [UpdateNotificationConfiguration](#)
- [UpdateOtaTask](#)

CreateAccountAssociation

Creates a new account association via the destination id.

Request Syntax

```
POST /account-associations HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "ConnectorDestinationId": "string",
  "Description": "string",
  "GeneralAuthorization": {
    "AuthMaterialName": "string"
  },
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

ConnectorDestinationId

The identifier of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Description

A description of the account association request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9- _]+

Required: No

GeneralAuthorization

The General Authorization reference by authorization material name.

Type: [GeneralAuthorizationName](#) object

Required: No

Name

The name of the destination for the new account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

Tags

A set of key/value pairs that are used to manage the account association.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "AccountAssociationId": "string",
  "Arn": "string",
  "AssociationState": "string",
  "OAuthAuthorizationUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

AccountAssociationId

The identifier for the account association request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Arn

The Amazon Resource Name (ARN) of the account association.

Type: String

Length Constraints: Minimum length of 67. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:account-association/[0-9a-zA-Z-]+`

AssociationState

The current state of the account association request.

Type: String

Valid Values: `ASSOCIATION_IN_PROGRESS` | `ASSOCIATION_FAILED` | `ASSOCIATION_SUCCEEDED` | `ASSOCIATION_DELETING` | `REFRESH_TOKEN_EXPIRED`

OAuthAuthorizationUrl

Third-party IoT platform OAuth authorization server URL backed with all the required parameters to perform end-user authentication. This field will be empty when using General Authorization flows that do not require OAuth.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `$|^(https):\\/.*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateCloudConnector

Creates a C2C (cloud-to-cloud) connector.

Request Syntax

```
POST /cloud-connectors HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Description": "string",
  "EndpointConfig": {
    "lambda": {
      "arn": "string"
    }
  },
  "EndpointType": "string",
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Description

A description of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Required: No

EndpointConfig

The configuration details for the cloud connector endpoint, including connection parameters and authentication requirements.

Type: [EndpointConfig](#) object

Required: Yes

EndpointType

The type of endpoint used for the cloud connector, which defines how the connector communicates with external services.

Type: String

Valid Values: LAMBDA

Required: No

Name

The display name of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The unique identifier assigned to the newly created cloud connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-__]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateConnectorDestination

Create a connector destination for connecting a cloud-to-cloud (C2C) connector to the customer's AWS account.

Request Syntax

POST /connector-destinations HTTP/1.1

Content-type: application/json

```
{
  "AuthConfig": {
    "GeneralAuthorization": [
      {
        "AuthMaterialName": "string",
        "SecretsManager": {
          "arn": "string",
          "versionId": "string"
        }
      }
    ],
    "oAuth": {
      "authUrl": "string",
      "oAuthCompleteRedirectUrl": "string",
      "proactiveRefreshTokenRenewal": {
        "DaysBeforeRenewal": number,
        "enabled": boolean
      },
      "scope": "string",
      "tokenEndpointAuthenticationScheme": "string",
      "tokenUrl": "string"
    }
  },
  "AuthType": "string",
  "ClientToken": "string",
  "CloudConnectorId": "string",
  "Description": "string",
  "Name": "string",
  "SecretsManager": {
    "arn": "string",
    "versionId": "string"
  }
}
```

```
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AuthConfig

The authentication configuration details for the connector destination, including OAuth settings and other authentication parameters.

Type: [AuthConfig](#) object

Required: Yes

AuthType

The authentication type used for the connector destination, which determines how credentials and access are managed.

Type: String

Valid Values: OAUTH

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9=_-]+`

Required: No

CloudConnectorId

The identifier of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Description

A description of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Name

The display name of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

SecretsManager

The AWS Secrets Manager configuration used to securely store and manage sensitive information for the connector destination.

Type: [SecretsManager](#) object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The identifier of the C2C connector destination creation request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateCredentialLocker

Create a credential locker.

Note

This operation will not trigger the creation of all the manufacturing resources.

Request Syntax

```
POST /credential-lockers HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Tags

A set of key/value pairs that are used to manage the credential locker.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "Arn": "string",
  "CreatedAt": number,
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

CreatedAt

The timestamp value of when the credential locker request occurred.

Type: Timestamp

Id

The identifier of the credential locker creation request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded for this request.

HTTP Status Code: 402

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateDestination

Create a notification destination such as Kinesis Data Streams that receive events and notifications from Managed integrations. Managed integrations uses the destination to determine where to deliver notifications.

Request Syntax

```
POST /destinations HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "Name": "string",
  "RoleArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+

Required: Yes

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: Yes

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: Yes

[RoleArn](#)

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Required: Yes

[Tags](#)

This parameter has been deprecated.

A set of key/value pairs that are used to manage the destination.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "Name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._- ]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateEventLogConfiguration

Set the event log configuration for the account, resource type, or specific resource.

Request Syntax

```
POST /event-log-configurations HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "EventLogLevel": "string",
  "ResourceId": "string",
  "ResourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: Yes

[ResourceId](#)

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

Required: No

[ResourceType](#)

The type of resource for the event log configuration.

Type: String

Pattern: [*]\$|^ (managed-thing|credential-locker|provisioning-profile|ota-task|account-association)

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The identifier of the event log configuration request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded for this request.

HTTP Status Code: 402

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateManagedThing

Creates a managed thing. A managed thing contains the device identifier, protocol supported, and capabilities of the device in a data model format defined by Managed integrations.

Request Syntax

POST /managed-things HTTP/1.1

Content-type: application/json

```
{
  "AuthenticationMaterial": "string",
  "AuthenticationMaterialType": "string",
  "Brand": "string",
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
            "id": "string",
            "name": "string",
            "properties": [ "string" ],
            "version": "string"
          }
        ],
        "deviceTypes": [ "string" ],
        "id": "string"
      }
    ],
    "nodeId": "string",
    "version": "string"
  },
  "CapabilitySchemas": [
    {
      "CapabilityId": "string",
      "ExtrinsicId": "string",
      "ExtrinsicVersion": number,
      "Format": "string",
      "Schema": JSON value
    }
  ]
}
```

```

],
"Classification": "string",
"ClientToken": "string",
"CredentialLockerId": "string",
"MetaData": {
  "string" : "string"
},
"Model": "string",
"Name": "string",
"Owner": "string",
"Role": "string",
"SerialNumber": "string",
"Tags": {
  "string" : "string"
},
"WiFiSimpleSetupConfiguration": {
  "EnableAsProvisionee": boolean,
  "EnableAsProvisioner": boolean,
  "TimeoutInMinutes": number
}
}

```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AuthenticationMaterial

The authentication material defining the device connectivity setup requests. The authorization materials used are the device bar code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: [0-9A-Za-z!#\$%&()*\+\-;<=>?@^_`{|}~\/: {},\\"]+

Required: Yes

AuthenticationMaterialType

The type of authentication material used for device connectivity setup requests.

Type: String

Valid Values: CUSTOM_PROTOCOL_QR_BAR_CODE | WIFI_SETUP_QR_BAR_CODE
| ZWAVE_QR_BAR_CODE | ZIGBEE_QR_BAR_CODE | DISCOVERED_DEVICE |
PRE_ONBOARDED_CLOUD

Required: Yes

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Capabilities

This parameter has been deprecated.

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { \$ } \ [\] = _ \ - \ +] +

Required: No

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

Required: No

CapabilitySchemas

The capability schemas that define the functionality and features supported by the managed thing, including device capabilities and their associated properties.

Type: Array of [CapabilitySchemaItem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

CredentialLockerId

The identifier of the credential for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

MetaData

The metadata for the managed thing.

Note

The managedThing metadata parameter is used for associating attributes with a managedThing that can be used for grouping over-the-air (OTA) tasks. Name value pairs in metadata can be used in the OtaTargetQueryString parameter for the CreateOtaTask API operation.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: `.*[a-zA-Z0-9_.,@/:#-]+.*`

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: `.*[a-zA-Z0-9_.,@/:#-]*.*`

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@- ]+`

Required: No

Role

The type of device used. This will be the hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

Required: Yes

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Required: No

Tags

A set of key/value pairs that are used to manage the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

WiFiSimpleSetupConfiguration

The Wi-Fi Simple Setup configuration for the managed thing, which defines provisioning capabilities and timeout settings.

Type: [WiFiSimpleSetupConfiguration](#) object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "CreatedAt": number,
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+`

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

Id

The id of the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateNotificationConfiguration

Creates a notification configuration. A configuration is a connection between an event type and a destination that you have already created.

Request Syntax

```
POST /notification-configurations HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "DestinationName": "string",
  "EventType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._- ]+`

Required: Yes

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: `DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT`

Required: Yes

Tags

This parameter has been deprecated.

A set of key/value pairs that are used to manage the notification configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
```



```
Content-type: application/json
```

```
{  
  "EventType": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[EventType](#)

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateOtaTask

Create an over-the-air (OTA) task to target a device.

Request Syntax

POST /ota-tasks HTTP/1.1

Content-type: application/json

```
{
  "ClientToken": "string",
  "Description": "string",
  "OtaMechanism": "string",
  "OtaSchedulingConfig": {
    "EndBehavior": "string",
    "EndTime": "string",
    "MaintenanceWindows": [
      {
        "DurationInMinutes": number,
        "StartTime": "string"
      }
    ],
    "StartTime": "string"
  },
  "OtaTargetQueryString": "string",
  "OtaTaskExecutionRetryConfig": {
    "RetryConfigCriteria": [
      {
        "FailureType": "string",
        "MinNumberOfRetries": number
      }
    ]
  },
  "OtaType": "string",
  "Protocol": "string",
  "S3Url": "string",
  "Tags": {
    "string" : "string"
  },
  "Target": [ "string" ],
  "TaskConfigurationId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

OtaMechanism

The deployment mechanism for the over-the-air (OTA) task.

Type: String

Valid Values: PUSH

Required: No

OtaSchedulingConfig

Over-the-air (OTA) task scheduling config.

Type: [OtaTaskSchedulingConfig](#) object

Required: No

OtaTargetQueryString

The query string to add things to the thing group.

Type: String

Required: No

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Type: [OtaTaskExecutionRetryConfig](#) object

Required: No

OtaType

The frequency type for the over-the-air (OTA) task.

Type: String

Valid Values: ONE_TIME | CONTINUOUS

Required: Yes

Protocol

The connection protocol the over-the-air (OTA) task uses to update the device.

Type: String

Valid Values: HTTP

Required: No

S3Url

The URL to the Amazon S3 bucket where the over-the-air (OTA) task is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Tags

A set of key/value pairs that are used to manage the over-the-air (OTA) task.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Target

The device targeted for the over-the-air (OTA) task.

Type: Array of strings

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Response Syntax

```
HTTP/1.1 201
```

```
Content-type: application/json
```

```
{  
  "Description": "string",  
  "TaskArn": "string",  
  "TaskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[Description](#)

A description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\ ]+`

[TaskArn](#)

The Amazon Resource Name (ARN) of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/[0-9a-zA-Z-]+`

[TaskId](#)

The identifier of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `[A-Za-z0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateOtaTaskConfiguration

Create a configuraiton for the over-the-air (OTA) task.

Request Syntax

POST /ota-task-configurations HTTP/1.1

Content-type: application/json

```
{
  "ClientToken": "string",
  "Description": "string",
  "Name": "string",
  "PushConfig": {
    "AbortConfig": {
      "AbortConfigCriteriaList": [
        {
          "Action": "string",
          "FailureType": "string",
          "MinNumberOfExecutedThings": number,
          "ThresholdPercentage": number
        }
      ]
    },
    "RolloutConfig": {
      "ExponentialRolloutRate": {
        "BaseRatePerMinute": number,
        "IncrementFactor": number,
        "RateIncreaseCriteria": {
          "numberOfNotifiedThings": number,
          "numberOfSucceededThings": number
        }
      },
      "MaximumPerMinute": number
    },
    "TimeoutConfig": {
      "InProgressTimeoutInMinutes": number
    }
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Description

A description of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Name

The name of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

[PushConfig](#)

Describes the type of configuration used for the over-the-air (OTA) task.

Type: [PushConfig](#) object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "TaskConfigurationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[TaskConfigurationId](#)

The identifier of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

CreateProvisioningProfile

Create a provisioning profile for executing device provisioning flows. The provisioning profile is a document that defines the set of resources and policies applied to a device during the provisioning process.

Request Syntax

```
POST /provisioning-profiles HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "CaCertificate": "string",
  "ClaimCertificate": "string",
  "ClientToken": "string",
  "Name": "string",
  "ProvisioningType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

CaCertificate

The body of the PEM-encoded certificate authority (CA) certificate.

Type: String

Pattern: -----BEGIN CERTIFICATE-----[\\s\\S]*-----END CERTIFICATE-----\\n?

Required: No

ClaimCertificate

The body of the PEM-encoded claim certificate. If a claim certificate is provided, it will be used for the provisioning profile. Otherwise, a claim certificate will be generated.

Type: String

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Name

The name of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [0-9A-Za-z_-]+

Required: No

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Required: Yes

Tags

A set of key/value pairs that are used to manage the provisioning profile.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "ClaimCertificate": "string",
  "ClaimCertificatePrivateKey": "string",
  "Id": "string",
  "Name": "string",
  "ProvisioningType": "string",
  "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

ClaimCertificate

The body of the PEM-encoded claim certificate.

Type: String

ClaimCertificatePrivateKey

The private key of the claim certificate. This may be stored securely on the device for validating the connection endpoint with IoT managed integrations using the public key.

Type: String

Id

The identifier of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9-_-]+`

Name

The name of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[0-9A-Za-z_-]+`

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: `FLEET_PROVISIONING` | `JITR`

Status

The status of a provisioning profile.

Type: String

Valid Values: CREATE_IN_PROGRESS | CREATE_FAILED | CREATED |
DELETE_IN_PROGRESS | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteAccountAssociation

Remove a third-party account association for an end user.

Note

You must first call the `DeregisterAccountAssociation` to remove the connection between the managed thing and the third-party account before calling the `DeleteAccountAssociation` API.

Request Syntax

```
DELETE /account-associations/AccountAssociationId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountAssociationId

The unique identifier of the account association to be deleted.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteCloudConnector

Delete a cloud connector.

Request Syntax

```
DELETE /cloud-connectors/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the cloud connector.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-_]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteConnectorDestination

Delete a connector destination linked to a cloud-to-cloud (C2C) connector.

Note

Deletion can't be done if the account association has used this connector destination.

Request Syntax

```
DELETE /connector-destinations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the connector destination.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-__]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteCredentialLocker

Delete a credential locker.

Note

This operation can't be undone and any existing device won't be able to use IoT managed integrations.

Request Syntax

```
DELETE /credential-lockers/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the credential locker.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteDestination

Deletes a notification destination specified by name.

Request Syntax

```
DELETE /destinations/Name HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Name

The id of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteEventLogConfiguration

Delete an event log configuration.

Request Syntax

```
DELETE /event-log-configurations/Id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Id

The identifier of the event log configuration.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteManagedThing

Delete a managed thing. For direct-connected and hub-connected devices connecting with Managed integrations via a controller, all of the devices connected to it will have their status changed to PENDING. It is not possible to remove a cloud-to-cloud device.

Request Syntax

```
DELETE /managed-things/Identifier?Force=Force HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Force

When set to TRUE, a forceful deletion of the managed thing will occur. When set to FALSE, a non-forceful deletion of the managed thing will occur.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteNotificationConfiguration

Deletes a notification configuration.

Request Syntax

```
DELETE /notification-configurations/EventType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventType

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteOtaTask

Delete the over-the-air (OTA) task.

Request Syntax

```
DELETE /ota-tasks/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the over-the-air (OTA) task.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

LimitExceededException

The request exceeds a service limit or quota. Adjust your request parameters and try again.

HTTP Status Code: 410

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteOtaTaskConfiguration

Delete the over-the-air (OTA) task configuration.

Request Syntax

```
DELETE /ota-task-configurations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the over-the-air (OTA) task configuration.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteProvisioningProfile

Delete a provisioning profile.

Request Syntax

```
DELETE /provisioning-profiles/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the provisioning profile.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-_]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeregisterAccountAssociation

Deregister an account association from a managed thing.

Request Syntax

```
PUT /managed-thing-associations/deregister HTTP/1.1
Content-type: application/json
```

```
{
  "AccountAssociationId": "string",
  "ManagedThingId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AccountAssociationId](#)

The unique identifier of the account association to be deregistered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: Yes

[ManagedThingId](#)

The identifier of the managed thing to be deregistered from the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetAccountAssociation

Get an account association for an AWS account linked to a customer-managed destination.

Request Syntax

```
GET /account-associations/AccountAssociationId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountAssociationId

The unique identifier of the account association to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AccountAssociationId": "string",
  "Arn": "string",
  "AssociationState": "string",
  "ConnectorDestinationId": "string",
  "Description": "string",
  "ErrorMessage": "string",
  "GeneralAuthorization": {
    "AuthMaterialName": "string"
```

```
{,
  "Name": "string",
  "OAuthAuthorizationUrl": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssociationId

The unique identifier of the retrieved account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Arn

The Amazon Resource Name (ARN) of the account association.

Type: String

Length Constraints: Minimum length of 67. Maximum length of 1011.

Pattern: arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:account-association/[0-9a-zA-Z-]+

AssociationState

The current status state for the account association.

Type: String

Valid Values: ASSOCIATION_IN_PROGRESS | ASSOCIATION_FAILED | ASSOCIATION_SUCCEEDED | ASSOCIATION_DELETING | REFRESH_TOKEN_EXPIRED

ConnectorDestinationId

The identifier of the connector destination associated with this account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Description

The description of the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9- _]+

ErrorMessage

The error message explaining the current account association error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9- _]+

GeneralAuthorization

The General Authorization reference by authorization material name.

Type: [GeneralAuthorizationName](#) object

Name

The name of the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

OAuthAuthorizationUrl

Third party IoT platform OAuth authorization server URL backed with all the required parameters to perform end-user authentication. This field will be empty when using General Authorization flows that do not require OAuth.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `$|^(https):\\/.*`

Tags

A set of key/value pairs that are used to manage the account association.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetCloudConnector

Get configuration details for a cloud connector.

Request Syntax

```
GET /cloud-connectors/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the C2C connector.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-__]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Description": "string",
  "EndpointConfig": {
    "lambda": {
      "arn": "string"
    }
  },
  "EndpointType": "string",
  "Id": "string",
```

```
"Name": "string",  
"Type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

A description of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

EndpointConfig

The configuration details for the cloud connector endpoint, including connection parameters and authentication requirements.

Type: [EndpointConfig](#) object

EndpointType

The type of endpoint used for the cloud connector, which defines how the connector communicates with external services.

Type: String

Valid Values: LAMBDA

Id

The unique identifier of the cloud connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Name

The display name of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Type

The type of cloud connector created.

Type: String

Valid Values: LISTED | UNLISTED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetConnectorDestination

Get connector destination details linked to a cloud-to-cloud (C2C) connector.

Request Syntax

```
GET /connector-destinations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the C2C connector destination.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "AuthConfig": {
    "GeneralAuthorization": [
      {
        "AuthMaterialName": "string",
        "SecretsManager": {
          "arn": "string",
          "versionId": "string"
        }
      }
    ]
  }
}
```

```
    ],  
    "oAuth": {  
      "authUrl": "string",  
      "oAuthCompleteRedirectUrl": "string",  
      "proactiveRefreshTokenRenewal": {  
        "DaysBeforeRenewal": number,  
        "enabled": boolean  
      },  
      "scope": "string",  
      "tokenEndpointAuthenticationScheme": "string",  
      "tokenUrl": "string"  
    },  
    "AuthType": "string",  
    "CloudConnectorId": "string",  
    "Description": "string",  
    "Id": "string",  
    "Name": "string",  
    "OAuthCompleteRedirectUrl": "string",  
    "SecretsManager": {  
      "arn": "string",  
      "versionId": "string"  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuthConfig

The authentication configuration details for the connector destination, including OAuth settings and other authentication parameters.

Type: [AuthConfig](#) object

AuthType

The authentication type used for the connector destination, which determines how credentials and access are managed.

Type: String

Valid Values: OAUTH

CloudConnectorId

The identifier of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Description

A description of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Id

The unique identifier of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Name

The display name of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

OAuthCompleteRedirectUrl

The URL where users are redirected after completing the OAuth authorization process for the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: (http|https)://.*

SecretsManager

The AWS Secrets Manager configuration used to securely store and manage sensitive information for the connector destination.

Type: SecretsManager object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetCredentialLocker

Get information on an existing credential locker

Request Syntax

```
GET /credential-lockers/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the credential locker.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string",
  "CreatedAt": number,
  "Id": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

CreatedAt

The timestamp value of when the credential locker request occurred.

Type: Timestamp

Id

The identifier of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Tags

A set of key/value pairs that are used to manage the credential locker.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetCustomEndpoint

Returns the IoT managed integrations custom endpoint.

Request Syntax

```
GET /custom-endpoint HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EndpointAddress": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EndpointAddress](#)

The IoT managed integrations dedicated, custom endpoint for the device to route traffic through.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._@-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDefaultEncryptionConfiguration

Retrieves information about the default encryption configuration for the AWS account in the default or specified region. For more information, see [Key management](#) in the *AWS IoT SiteWise User Guide*.

Request Syntax

```
GET /configuration/account/encryption HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

Provides the status of the default encryption configuration for an AWS account.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION |
CUSTOMER_KEY_ENCRYPTION

kmsKeyArn

The Key Amazon Resource Name (ARN) of the AWS AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDestination

Gets a destination by name.

Request Syntax

```
GET /destinations/Name HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Name

The name of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "Name": "string",
  "RoleArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

```
} ,  
  "UpdatedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the destination creation request occurred.

Type: Timestamp

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._- ]+`

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\ ]+`

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

RoleArn

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Tags

This parameter has been deprecated.

A set of key/value pairs that are used to manage the customer-managed destination.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UpdatedAt

The timestamp value of when the destination update request occurred.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDeviceDiscovery

Get the current state of a device discovery.

Request Syntax

```
GET /device-discoveries/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the device discovery job request.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "AccountAssociationId": "string",
  "Arn": "string",
  "ConnectorAssociationId": "string",
  "ControllerId": "string",
  "DiscoveryType": "string",
  "FinishedAt": number,
  "Id": "string",
  "StartedAt": number,
  "Status": "string",
```

```
"Tags": {  
  "string" : "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssociationId

The identifier of the account association used for the device discovery.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Arn

The Amazon Resource Name (ARN) of the device discovery job request.

Type: String

Pattern: arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:device-discovery/[0-9a-zA-Z-]+

ConnectorAssociationId

This parameter has been deprecated.

The ID tracking the current discovery process for one connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z-]+

ControllerId

The id of the end-user's IoT hub.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

DiscoveryType

The discovery type supporting the type of device to be discovered in the device discovery job request.

Type: String

Valid Values: ZWAVE | ZIGBEE | CLOUD | CUSTOM |
CONTROLLER_CAPABILITY_REDISCOVERY

FinishedAt

The timestamp value for the completion time of the device discovery.

Type: Timestamp

Id

The id of the device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

StartedAt

The timestamp value for the start time of the device discovery.

Type: Timestamp

Status

The status of the device discovery job request.

Type: String

Valid Values: RUNNING | SUCCEEDED | FAILED | TIMED_OUT

Tags

This parameter has been deprecated.

A set of key/value pairs that are used to manage the device discovery request.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetEventLogConfiguration

Get an event log configuration.

Request Syntax

```
GET /event-log-configurations/Id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Id

The identifier of the event log configuration.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EventLogLevel": "string",
  "Id": "string",
  "ResourceId": "string",
  "ResourceType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Id

The identifier of the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

ResourceId

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

ResourceType

The type of resource for the event log configuration.

Type: String

Pattern: [*]\$|^((managed-thing|credential-locker|provisioning-profile|ota-task|account-association))

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetHubConfiguration

Get a hub configuration.

Request Syntax

```
GET /hub-configuration HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number,
  "UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[HubTokenTimerExpirySettingInSeconds](#)

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

UpdatedAt

The timestamp value of when the hub configuration was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThing

Get details of a managed thing including its attributes and capabilities.

Request Syntax

```
GET /managed-things/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ActivatedAt": number,
  "AdvertisedProductId": "string",
  "Arn": "string",
  "Brand": "string",
  "Classification": "string",
  "ConnectorDestinationId": "string",
  "ConnectorDeviceId": "string",
  "ConnectorPolicyId": "string",
```

```
"CreatedAt": number,
"CredentialLockerId": "string",
"DeviceSpecificKey": "string",
"HubNetworkMode": "string",
"Id": "string",
"InternationalArticleNumber": "string",
"MacAddress": "string",
"MetaData": {
  "string" : "string"
},
"Model": "string",
"Name": "string",
"Owner": "string",
"ParentControllerId": "string",
"ProvisioningStatus": "string",
"Role": "string",
"SerialNumber": "string",
"Tags": {
  "string" : "string"
},
"UniversalProductCode": "string",
"UpdatedAt": number,
"WiFiSimpleSetupConfiguration": {
  "EnableAsProvisionee": boolean,
  "EnableAsProvisioner": boolean,
  "TimeoutInMinutes": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActivatedAt

The timestamp value of when the device was activated.

Type: Timestamp

AdvertisedProductId

The id of the advertised product.

Type: String

Length Constraints: Fixed length of 5.

Pattern: ([A-Za-z0-9!#\$%&()*\+\-;=>?@^_`{|}~])+

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

ConnectorDestinationId

The identifier of the connector destination associated with this managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-__]+

ConnectorDeviceId

The third-party device id as defined by the connector. This device id must not contain personal identifiable information (PII).

 Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

ConnectorPolicyId

This parameter has been deprecated.

The id of the connector policy.

 Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

CredentialLockerId

The identifier of the credential locker for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

DeviceSpecificKey

A Zwave device-specific key used during device activation.

Note

This parameter is used for Zwave devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9=_.,@+\-]+`

HubNetworkMode

The network mode for the hub-connected device.

Type: String

Valid Values: STANDARD | NETWORK_WIDE_EXCLUSION

Id

The id of the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

InternationalArticleNumber

The unique 13 digit number that identifies the managed thing.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 13.

Pattern: `[0-9]+`

MacAddress

The media access control (MAC) address for the device represented by the managed thing.

Note

This parameter is used for Zigbee devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: `.*[a-zA-Z0-9_.,@/:#-]+.*`

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: `.*[a-zA-Z0-9_.,@/:#-]*.*`

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@- ]+`

ParentControllerId

Id of the controller device used for the discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9 ]+`

ProvisioningStatus

The provisioning status of the device in the provisioning workflow for onboarding to IoT managed integrations. For more information, see [Device Provisioning](#).

Type: String

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED | DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

Role

The type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Tags

A set of key/value pairs that are used to manage the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UniversalProductCode

The universal product code (UPC) of the device model. The UPC is typically used in the United States of America and Canada.

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]+

UpdatedAt

The timestamp value of when the managed thing was last updated at.

Type: Timestamp

WiFiSimpleSetupConfiguration

The Wi-Fi Simple Setup configuration for the managed thing, which defines provisioning capabilities and timeout settings.

Type: [WiFiSimpleSetupConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingCapabilities

Get the capabilities for a managed thing using the device ID.

Request Syntax

```
GET /managed-things-capabilities/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
```

```
        "id": "string",
        "name": "string",
        "properties": [ "string" ],
        "version": "string"
      }
    ],
    "deviceTypes": [ "string" ],
    "id": "string"
  }
],
  "nodeId": "string",
  "version": "string"
},
  "ManagedThingId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Capabilities

This parameter has been deprecated.

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { \$ } \ [\] = _ \ - \ +] +

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

ManagedThingId

The id of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingCertificate

Retrieves the certificate PEM for a managed IoT thing.

Request Syntax

```
GET /managed-things-certificate/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CertificatePem": "string",
  "ManagedThingId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CertificatePem

The PEM-encoded certificate for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: `[\s\S]*`

ManagedThingId

The identifier of the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingConnectivityData

Get the connectivity status of a managed thing.

Request Syntax

```
POST /managed-things-connectivity-data/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Connected": boolean,
  "DisconnectReason": "string",
  "ManagedThingId": "string",
  "Timestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connected

The connectivity status for a managed thing.

Type: Boolean

DisconnectReason

The reason for the connectivity disconnect with the managed thing.

Type: String

Valid Values: AUTH_ERROR | CLIENT_INITIATED_DISCONNECT | CLIENT_ERROR
| CONNECTION_LOST | DUPLICATE_CLIENTID | FORBIDDEN_ACCESS |
MQTT_KEEP_ALIVE_TIMEOUT | SERVER_ERROR | SERVER_INITIATED_DISCONNECT
| THROTTLED | WEBSOCKET_TTL_EXPIRATION | CUSTOMAUTH_TTL_EXPIRATION |
UNKNOWN | NONE

ManagedThingId

The id of a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Timestamp

The timestamp value of when the connectivity status for a managed thing was last taken.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingMetaData

Get the metadata information for a managed thing.

Note

The managedThing metadata parameter is used for associating attributes with a managedThing that can be used for grouping over-the-air (OTA) tasks. Name value pairs in metadata can be used in the OtaTargetQueryString parameter for the CreateOtaTask API operation.

Request Syntax

```
GET /managed-things-metadata/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The managed thing id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```



```
{
  "ManagedThingId": "string",
  "MetaData": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManagedThingId

The managed thing id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: .*[a-zA-Z0-9_.,@/:#-]+.*

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: .*[a-zA-Z0-9_.,@/:#-]*.*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingState

Returns the managed thing state for the given device Id.

Request Syntax

```
GET /managed-thing-states/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Endpoints": [
    {
      "capabilities": [
        {
          "id": "string",
          "name": "string",
          "properties": JSON value,
          "version": "string"
        }
      ]
    }
  ]
}
```

```
    ],  
    "endpointId": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Endpoints

The device endpoint.

Type: Array of [StateEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetNotificationConfiguration

Get a notification configuration for a specified event type.

Request Syntax

```
GET /notification-configurations/EventType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventType

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "CreatedAt": number,  
  "DestinationName": "string",  
  "EventType": "string",  
  "Tags": {  
    "string" : "string"  
  },  
}
```

```
"UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the notification configuration was created.

Type: Timestamp

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT

Tags

This parameter has been deprecated.

A set of key/value pairs that are used to manage the notification configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UpdatedAt

The timestamp value of when the notification configuration was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetOtaTask

Get details of the over-the-air (OTA) task by its task id.

Request Syntax

```
GET /ota-tasks/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "CreatedAt": number,
  "Description": "string",
  "LastUpdatedAt": number,
  "OtaMechanism": "string",
  "OtaSchedulingConfig": {
    "EndBehavior": "string",
    "EndTime": "string",
    "MaintenanceWindows": [
      {
        "DurationInMinutes": number,
```

```

        "StartTime": "string"
    },
    ],
    "StartTime": "string"
},
"OtaTargetQueryString": "string",
"OtaTaskExecutionRetryConfig": {
    "RetryConfigCriteria": [
        {
            "FailureType": "string",
            "MinNumberOfRetries": number
        }
    ]
},
"OtaType": "string",
"Protocol": "string",
"S3Url": "string",
"Status": "string",
"Tags": {
    "string" : "string"
},
"Target": [ "string" ],
"TaskArn": "string",
"TaskConfigurationId": "string",
"TaskId": "string",
"TaskProcessingDetails": {
    "NumberOfCanceledThings": number,
    "NumberOfFailedThings": number,
    "NumberOfInProgressThings": number,
    "numberOfQueuedThings": number,
    "numberOfRejectedThings": number,
    "numberOfRemovedThings": number,
    "numberOfSucceededThings": number,
    "numberOfTimedOutThings": number,
    "processingTargets": [ "string" ]
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the over-the-air (OTA) task was created.

Type: Timestamp

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task was last updated at.

Type: Timestamp

OtaMechanism

The deployment mechanism for the over-the-air (OTA) task.

Type: String

Valid Values: PUSH

OtaSchedulingConfig

Over-the-air (OTA) task scheduling config.

Type: [OtaTaskSchedulingConfig](#) object

OtaTargetQueryString

The query string to add things to the thing group.

Type: String

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Type: [OtaTaskExecutionRetryConfig](#) object

OtaType

The frequency type for the over-the-air (OTA) task.

Type: String

Valid Values: ONE_TIME | CONTINUOUS

Protocol

The connection protocol the over-the-air (OTA) task uses to update the device.

Type: String

Valid Values: HTTP

S3Url

The URL to the Amazon S3 bucket where the over-the-air (OTA) task is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Status

The status of the over-the-air (OTA) task.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED | DELETION_IN_PROGRESS | SCHEDULED

Tags

A set of key/value pairs that are used to manage the over-the-air (OTA) task.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Target

The device targeted for the over-the-air (OTA) task.

Type: Array of strings

TaskArn

The Amazon Resource Name (ARN) of the over-the-air (OTA) task

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/[0-9a-zA-Z-]+`

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

TaskId

The id of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `[A-Za-z0-9]+`

TaskProcessingDetails

The processing details of all over-the-air (OTA) tasks.

Type: [TaskProcessingDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetOtaTaskConfiguration

Get a configuraiton for the over-the-air (OTA) task.

Request Syntax

```
GET /ota-task-configurations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task configuration id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "Description": "string",
  "Name": "string",
  "PushConfig": {
    "AbortConfig": {
      "AbortConfigCriteriaList": [
        {
          "Action": "string",
          "FailureType": "string",
```

```
        "MinNumberOfExecutedThings": number,
        "ThresholdPercentage": number
      }
    ]
  },
  "RolloutConfig": {
    "ExponentialRolloutRate": {
      "BaseRatePerMinute": number,
      "IncrementFactor": number,
      "RateIncreaseCriteria": {
        "numberOfNotifiedThings": number,
        "numberOfSucceededThings": number
      }
    },
    "MaximumPerMinute": number
  },
  "TimeoutConfig": {
    "InProgressTimeoutInMinutes": number
  }
},
"TaskConfigurationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the over-the-air (OTA) task configuration was created at.

Type: Timestamp

Description

A description of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Name

The name of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

PushConfig

Describes the type of configuration used for the over-the-air (OTA) task.

Type: [PushConfig](#) object

TaskConfigurationId

The over-the-air (OTA) task configuration id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetProvisioningProfile

Get details of a provisioning profile.

Request Syntax

```
GET /provisioning-profiles/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of a provisioning profile.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ClaimCertificate": "string",
  "Id": "string",
  "Name": "string",
  "ProvisioningType": "string",
  "Status": "string",
  "Tags": {
    "string" : "string"
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

ClaimCertificate

The body of the PEM-encoded claim certificate.

Type: String

Id

The provisioning profile id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9-_-]+`

Name

The name of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[0-9A-Za-z-_]+`

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Status

The status of a provisioning profile.

Type: String

Valid Values: CREATE_IN_PROGRESS | CREATE_FAILED | CREATED | DELETE_IN_PROGRESS | DELETE_FAILED

Tags

A set of key/value pairs that are used to manage the provisioning profile.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetRuntimeLogConfiguration

Get the runtime log configuration for a specific managed thing.

Request Syntax

```
GET /runtime-log-configurations/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ManagedThingId": "string",
  "RuntimeLogConfigurations": {
    "DeleteLocalStoreAfterUpload": boolean,
    "LocalStoreFileRotationMaxBytes": number,
    "LocalStoreFileRotationMaxFiles": number,
    "LocalStoreLocation": "string",
    "LogFlushLevel": "string",
    "LogLevel": "string",
```

```
"UploadLog": boolean,  
"UploadPeriodMinutes": number  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManagedThingId

The id for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

RuntimeLogConfigurations

The runtime log configuration for a managed thing.

Type: [RuntimeLogConfigurations](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetSchemaVersion

Gets a schema version with the provided information.

Request Syntax

```
GET /schema-versions/Type/SchemaVersionedId?Format=Format HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Format

The format of the schema version.

Valid Values: AWS | ZCL | CONNECTOR

SchemaVersionedId

Schema id with a version specified. If the version is missing, it defaults to latest version.

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?|\$latest)`

Required: Yes

Type

The type of schema version.

Valid Values: capability | definition

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "Description": "string",
  "Namespace": "string",
  "Schema": JSON value,
  "SchemaId": "string",
  "SemanticVersion": "string",
  "Type": "string",
  "Visibility": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The description of the schema version.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: [a-zA-Z0-9., / -]+

Namespace

The name of the schema version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: [a-z0-9]+

Schema

The schema of the schema version.

Type: JSON value

Schemald

The id of the schema version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: [a-zA-Z0-9.]+

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: (\d+\.\d+(\.\d+)?|\\$latest)

Type

The type of schema version.

Type: String

Valid Values: capability | definition

Visibility

The visibility of the schema version.

Type: String

Valid Values: PUBLIC | PRIVATE

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListAccountAssociations

Lists all account associations, with optional filtering by connector destination ID.

Request Syntax

```
GET /account-associations?  
ConnectorDestinationId=ConnectorDestinationId&MaxResults=MaxResults&NextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectorDestinationId

The identifier of the connector destination to filter account associations by.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

MaxResults

The maximum number of account associations to return in a single response.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token used for pagination of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "Items": [
    {
      "AccountAssociationId": "string",
      "Arn": "string",
      "AssociationState": "string",
      "ConnectorDestinationId": "string",
      "Description": "string",
      "ErrorMessage": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of account associations that match the specified criteria.

Type: Array of [AccountAssociationItem](#) objects

NextToken

A token used for pagination of results when there are more account associations than can be returned in a single response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListCloudConnectors

Returns a list of connectors filtered by its AWS Lambda Amazon Resource Name (ARN) and type.

Request Syntax

```
GET /cloud-connectors?  
LambdaArn=LambdaArn&MaxResults=MaxResults&NextToken=NextToken&Type=Type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

LambdaArn

The Amazon Resource Name (ARN) of the Lambda function to filter cloud connectors by.

Pattern: (arn:aws:lambda:[0-9a-zA-Z-]+:[0-9]+:function:)?([a-zA-Z0-9-_]+(:(\\$LATEST|[a-zA-Z0-9-_]+))?)

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Type

The type of cloud connectors to filter by when listing available connectors.

Valid Values: LISTED | UNLISTED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Description": "string",
      "EndpointConfig": {
        "lambda": {
          "arn": "string"
        }
      },
      "EndpointType": "string",
      "Id": "string",
      "Name": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of connectors.

Type: Array of [ConnectorItem](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListConnectorDestinations

Lists all connector destinations, with optional filtering by cloud connector ID.

Request Syntax

```
GET /connector-destinations?  
CloudConnectorId=CloudConnectorId&MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CloudConnectorId

The identifier of the cloud connector to filter connector destinations by.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

MaxResults

The maximum number of connector destinations to return in a single response.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token used for pagination of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9= _-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "ConnectorDestinationList": [
    {
      "CloudConnectorId": "string",
      "Description": "string",
      "Id": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectorDestinationList](#)

The list of connector destinations that match the specified criteria.

Type: Array of [ConnectorDestinationSummary](#) objects

[NextToken](#)

A token used for pagination of results when there are more connector destinations than can be returned in a single response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListCredentialLockers

List information on an existing credential locker.

Request Syntax

```
GET /credential-lockers?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Arn": "string",
      "CreatedAt": number,
```

```
    "Id": "string",  
    "Name": "string"  
  },  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of credential lockers.

Type: Array of [CredentialLockerSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDestinations

List all notification destinations.

Request Syntax

```
GET /destinations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DestinationList": [
    {
      "DeliveryDestinationArn": "string",
      "DeliveryDestinationType": "string",
      "Description": "string",
```

```
    "Name": "string",  
    "RoleArn": "string"  
  },  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DestinationList](#)

The list of destinations.

Type: Array of [DestinationSummary](#) objects

[NextToken](#)

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDeviceDiscoveries

Lists all device discovery tasks, with optional filtering by type and status.

Request Syntax

```
GET /device-discoveries?  
MaxResults=MaxResults&NextToken=NextToken&StatusFilter=StatusFilter&TypeFilter=TypeFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of device discovery jobs to return in a single response.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token used for pagination of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

StatusFilter

The status to filter device discovery jobs by.

Valid Values: RUNNING | SUCCEEDED | FAILED | TIMED_OUT

TypeFilter

The discovery type to filter device discovery jobs by.

Valid Values: ZWAVE | ZIGBEE | CLOUD | CUSTOM |
CONTROLLER_CAPABILITY_REDISCOVERY

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "DiscoveryType": "string",
      "Id": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of device discovery jobs that match the specified criteria.

Type: Array of [DeviceDiscoverySummary](#) objects

NextToken

A token used for pagination of results when there are more device discovery jobs than can be returned in a single response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDiscoveredDevices

Lists all devices discovered during a specific device discovery task.

Request Syntax

```
GET /device-discoveries/Identifier/devices?MaxResults=MaxResults&NextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the device discovery job to list discovered devices for.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

MaxResults

The maximum number of discovered devices to return in a single response.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token used for pagination of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "AuthenticationMaterial": "string",
      "Brand": "string",
      "ConnectorDeviceId": "string",
      "ConnectorDeviceName": "string",
      "DeviceTypes": [ "string" ],
      "DiscoveredAt": number,
      "ManagedThingId": "string",
      "Model": "string",
      "Modification": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of discovered devices that match the specified criteria.

Type: Array of [DiscoveredDeviceSummary](#) objects

NextToken

A token used for pagination of results when there are more discovered devices than can be returned in a single response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListEventLogConfigurations

List all event log configurations for an account.

Request Syntax

```
GET /event-log-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EventLogConfigurationList": [
    {
      "EventLogLevel": "string",
      "Id": "string",
```

```
    "ResourceId": "string",  
    "ResourceType": "string"  
  },  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EventLogConfigurationList](#)

A list of each event log configuration and pertinent information.

Type: Array of [EventLogConfigurationSummary](#) objects

[NextToken](#)

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListManagedThingAccountAssociations

Lists all account associations for a specific managed thing.

Request Syntax

```
GET /managed-thing-associations?  
AccountAssociationId=AccountAssociationId&ManagedThingId=ManagedThingId&MaxResults=MaxResults&N  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountAssociationId

The identifier of the account association to filter results by. When specified, only associations with this account association ID will be returned.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

ManagedThingId

The identifier of the managed thing to list account associations for.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

MaxResults

The maximum number of account associations to return in a single response.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token used for pagination of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "AccountAssociationId": "string",
      "ManagedThingAssociationStatus": "string",
      "ManagedThingId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of managed thing associations that match the specified criteria, including the managed thing ID and account association ID for each association.

Type: Array of [ManagedThingAssociation](#) objects

NextToken

A token used for pagination of results when there are more account associations than can be returned in a single response.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListManagedThings

Listing all managed things with provision for filters.

Request Syntax

```
GET /managed-things?  
ConnectorDestinationIdFilter=ConnectorDestinationIdFilter&ConnectorDeviceIdFilter=ConnectorDeviceIdFilter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectorDestinationIdFilter

Filter managed things by the connector destination ID they are associated with.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

ConnectorDeviceIdFilter

Filter managed things by the connector device ID they are associated with. When specified, only managed things with this connector device ID will be returned.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

ConnectorPolicyIdFilter

This parameter has been deprecated.

Filter on a connector policy id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

CredentialLockerFilter

Filter on a credential locker for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

OwnerFilter

Filter on device owners when listing managed things.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.,@-]+

ParentControllerIdentifierFilter

Filter on a parent controller id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9]+

ProvisioningStatusFilter

Filter on the status of the device. For more information, see [Device Provisioning](#).

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED |
DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

RoleFilter

Filter on the type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Valid Values: CONTROLLER | DEVICE

SerialNumberFilter

Filter on the serial number of the device.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "ActivatedAt": number,
      "AdvertisedProductId": "string",
      "Arn": "string",
      "Brand": "string",
      "Classification": "string",
      "ConnectorDestinationId": "string",
      "ConnectorDeviceId": "string",
      "ConnectorPolicyId": "string",
      "CreatedAt": number,
      "CredentialLockerId": "string",
      "Id": "string",
      "Model": "string",
      "Name": "string",
      "Owner": "string",
      "ParentControllerId": "string",
      "ProvisioningStatus": "string",
      "Role": "string",
      "SerialNumber": "string",
      "UpdatedAt": number
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of managed things.

Type: Array of [ManagedThingSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListManagedThingSchemas

List schemas associated with a managed thing.

Request Syntax

```
GET /managed-thing-schemas/Identifier?  
CapabilityIdFilter=CapabilityIdFilter&EndpointIdFilter=EndpointIdFilter&MaxResults=MaxResults&N  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapabilityIdFilter

Filter on a capability id.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9./]+(@\d+\\.\\d+)?`

EndpointIdFilter

Filter on an endpoint id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Identifier

The managed thing id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: Yes

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

[NextToken](#)

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: `[a-zA-Z0-9=_-]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "CapabilityId": "string",
      "EndpointId": "string",
      "Schema": JSON value
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Items](#)

The list of managed thing schemas.

Type: Array of [ManagedThingSchemaListItem](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListNotificationConfigurations

List all notification configurations.

Request Syntax

```
GET /notification-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "NotificationConfigurationList": [
    {
      "DestinationName": "string",
```

```
    "EventType": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

NotificationConfigurationList

The list of notification configurations.

Type: Array of [NotificationConfigurationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOtaTaskConfigurations

List all of the over-the-air (OTA) task configurations.

Request Syntax

```
GET /ota-task-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "CreatedAt": number,
      "Name": "string",
      "TaskConfigurationId": "string"
    }
  ]
}
```

```
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of the over-the-air (OTA) task configurations.

Type: Array of [OtaTaskConfigurationSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOtaTaskExecutions

List all of the over-the-air (OTA) task executions.

Request Syntax

```
GET /ota-tasks/Identifier/devices?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "ExecutionSummaries": [
    {
      "ManagedThingId": "string",
      "TaskExecutionSummary": {
        "ExecutionNumber": number,
        "LastUpdatedAt": number,
        "QueuedAt": number,
        "RetryAttempt": number,
        "StartedAt": number,
        "Status": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExecutionSummaries

A list of all of the over-the-air (OTA) task executions.

Type: Array of [OtaTaskExecutionSummaries](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOtaTasks

List all of the over-the-air (OTA) tasks.

Request Syntax

```
GET /ota-tasks?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Tasks": [
    {
      "CreatedAt": number,
      "LastUpdatedAt": number,
```

```
    "Status": "string",  
    "TaskArn": "string",  
    "TaskConfigurationId": "string",  
    "TaskId": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Tasks

A list of all of the over-the-air (OTA) tasks.

Type: Array of [OtaTaskSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListProvisioningProfiles

List the provisioning profiles within the AWS account.

Request Syntax

```
GET /provisioning-profiles?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: `[a-zA-Z0-9=_-]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Items": [
    {
      "Arn": "string",
      "Id": "string",
      "Name": "string",
```

```
    "ProvisioningType": "string",  
    "Status": "string"  
  },  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of provisioning profiles.

Type: Array of [ProvisioningProfileSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSchemaVersions

Lists schema versions with the provided information.

Request Syntax

```
GET /schema-versions/Type?  
MaxResults=MaxResults&NamespaceFilter=Namespace&NextToken=NextToken&SchemaIdFilter=SchemaId&Sem  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

Namespace

Filter on the name of the schema version.

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: [a-z0-9]+

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

SchemaId

Filter on the id of the schema version.

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: [a-zA-Z0-9.]+

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: `(\d+\.\d+(\.\d+)?|\$latest)`

Type

Filter on the type of schema version.

Valid Values: `capability` | `definition`

Required: Yes

Visibility

The visibility of the schema version.

Valid Values: `PUBLIC` | `PRIVATE`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Description": "string",
      "Namespace": "string",
      "SchemaId": "string",
      "SemanticVersion": "string",
      "Type": "string",
      "Visibility": "string"
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of schema versions.

Type: Array of [SchemaVersionListItem](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for a specified resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource for which to list tags.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:(managed-thing|provisioning-profile|ota-task|credential-locker|account-association)/[0-9a-zA-Z-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A set of key/value pairs that are used to manage the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidRequestException

The request is not valid.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutDefaultEncryptionConfiguration

Sets the default encryption configuration for the AWS account. For more information, see [Key management](#) in the AWS IoT SiteWise User Guide.

Request Syntax

```
POST /configuration/account/encryption HTTP/1.1
Content-type: application/json

{
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[encryptionType](#)

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION |
CUSTOMER_KEY_ENCRYPTION

Required: Yes

[kmsKeyArn](#)

The Key Amazon Resource Name (ARN) of the AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+`

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

configurationStatus

Provides the status of the default encryption configuration for an AWS account.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION |
CUSTOMER_KEY_ENCRYPTION

kmsKeyArn

The Key Amazon Resource Name (ARN) of the AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutHubConfiguration

Update a hub configuration.

Request Syntax

```
PUT /hub-configuration HTTP/1.1
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

HubTokenTimerExpirySettingInSeconds

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number
}
```


Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

HubTokenTimerExpirySettingInSeconds

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutRuntimeLogConfiguration

Set the runtime log configuration for a specific managed thing.

Request Syntax

```
PUT /runtime-log-configurations/ManagedThingId HTTP/1.1
Content-type: application/json
```

```
{
  "RuntimeLogConfigurations": {
    "DeleteLocalStoreAfterUpload": boolean,
    "LocalStoreFileRotationMaxBytes": number,
    "LocalStoreFileRotationMaxFiles": number,
    "LocalStoreLocation": "string",
    "LogFlushLevel": "string",
    "LogLevel": "string",
    "UploadLog": boolean,
    "UploadPeriodMinutes": number
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

[RuntimeLogConfigurations](#)

The runtime log configuration for a managed thing.

Type: [RuntimeLogConfigurations](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

RegisterAccountAssociation

Registers an account association with a managed thing, establishing a connection between a device and a third-party account.

Request Syntax

```
PUT /managed-thing-associations/register HTTP/1.1
Content-type: application/json
```

```
{
  "AccountAssociationId": "string",
  "DeviceDiscoveryId": "string",
  "ManagedThingId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AccountAssociationId](#)

The identifier of the account association to register with the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: Yes

[DeviceDiscoveryId](#)

The identifier of the device discovery job associated with this registration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

ManagedThingId

The identifier of the managed thing to register with the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "AccountAssociationId": "string",
  "DeviceDiscoveryId": "string",
  "ManagedThingId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

AccountAssociationId

The identifier of the account association that was registered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

DeviceDiscoveryId

The identifier of the device discovery job associated with this registration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

ManagedThingId

The identifier of the managed thing that was registered with the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

RegisterCustomEndpoint

Customers can request IoT managed integrations to manage the server trust for them or bring their own external server trusts for the custom domain. Returns an IoT managed integrations endpoint.

Request Syntax

```
POST /custom-endpoint HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "EndpointAddress": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[EndpointAddress](#)

The IoT managed integrations dedicated, custom endpoint for the device to route traffic through.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._@-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ResetRuntimeLogConfiguration

Reset a runtime log configuration for a specific managed thing.

Request Syntax

```
DELETE /runtime-log-configurations/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

SendConnectorEvent

Relays third-party device events for a connector such as a new device or a device state change event.

Request Syntax

POST /connector-event/*ConnectorId* HTTP/1.1

Content-type: application/json

```
{
  "ConnectorDeviceId": "string",
  "DeviceDiscoveryId": "string",
  "Devices": [
    {
      "CapabilityReport": {
        "endpoints": [
          {
            "clientClusters": [ "string" ],
            "clusters": [
              {
                "attributes": [
                  {
                    "id": "string",
                    "name": "string",
                    "value": JSON value
                  }
                ],
                "commands": [ "string" ],
                "events": [ "string" ],
                "fabricIndex": number,
                "featureMap": number,
                "generatedCommands": [ "string" ],
                "id": "string",
                "name": "string",
                "publicId": "string",
                "revision": number,
                "specVersion": "string"
              }
            ],
            "deviceTypes": [ "string" ],
            "id": "string",
            "parts": [ "string" ],
```



```

        "semanticTags": [ "string" ]
      }
    ],
    "nodeId": "string",
    "version": "string"
  },
  "CapabilitySchemas": [
    {
      "CapabilityId": "string",
      "ExtrinsicId": "string",
      "ExtrinsicVersion": number,
      "Format": "string",
      "Schema": JSON value
    }
  ],
  "ConnectorDeviceId": "string",
  "ConnectorDeviceName": "string",
  "DeviceMetadata": JSON value
}
],
"MatterEndpoint": {
  "clusters": [
    {
      "attributes": JSON value,
      "commands": {
        "string" : JSON value
      },
      "events": {
        "string" : JSON value
      },
      "id": "string"
    }
  ],
  "id": "string"
},
"Message": "string",
"Operation": "string",
"OperationVersion": "string",
"StatusCode": number,
"TraceId": "string",
"UserId": "string"
}

```

URI Request Parameters

The request uses the following URI parameters.

ConnectorId

The id of the connector between the third-party cloud provider and IoT managed integrations.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConnectorDeviceId

The third-party device id as defined by the connector. This device id must not contain personal identifiable information (PII).

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

DeviceDiscoveryId

The id for the device discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: No

Devices

The list of devices.

Type: Array of [Device](#) objects

Required: No

MatterEndpoint

The device endpoint.

Type: [MatterEndpoint](#) object

Required: No

Message

The device state change event payload.

This parameter will include the following three fields:

- uri: schema auc://<PARTNER-DEVICE-ID>/ResourcePath (The Resourcepath corresponds to an OCF resource.)
- op: For device state changes, this field must populate as n+d.
- cn: The content depends on the OCF resource referenced in ResourcePath.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\sa-zA-Z0-9_.,@-]+

Required: No

Operation

The Open Connectivity Foundation (OCF) operation requested to be performed on the managed thing.

Note

The field op can have a value of "I" or "U". The field "cn" will contain the capability types.

Type: String

Valid Values: DEVICE_COMMAND_RESPONSE | DEVICE_DISCOVERY | DEVICE_EVENT |
DEVICE_COMMAND_REQUEST

Required: Yes

OperationVersion

The Open Connectivity Foundation (OCF) security specification version for the operation being requested on the managed thing. For more information, see [OCF Security Specification](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 6.

Pattern: [0-9.]+

Required: No

StatusCode

The status code of the Open Connectivity Foundation (OCF) operation being performed on the managed thing.

Type: Integer

Valid Range: Minimum value of 100. Maximum value of 550.

Required: No

TraceId

The trace request identifier. This is generated by IoT managed integrations and can be used to trace this command and its related operations in CloudWatch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9:=-_]+

Required: No

UserId

The id of the third-party cloud provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "ConnectorId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

ConnectorId

The id of the connector between the third-party cloud provider and IoT managed integrations.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-__]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

SendManagedThingCommand

Send the command to the device represented by the managed thing.

Request Syntax

POST /managed-things-command/*ManagedThingId* HTTP/1.1
Content-type: application/json

```
{
  "AccountAssociationId": "string",
  "ConnectorAssociationId": "string",
  "Endpoints": [
    {
      "capabilities": [
        {
          "actions": [
            {
              "actionTraceId": "string",
              "name": "string",
              "parameters": JSON value,
              "ref": "string"
            }
          ],
          "id": "string",
          "name": "string",
          "version": "string"
        }
      ],
      "endpointId": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

AccountAssociationId

The identifier of the account association to use when sending a command to a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

ConnectorAssociationId

This parameter has been deprecated.

The ID tracking the current discovery process for one connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

Endpoints

The device endpoint.

Type: Array of [CommandEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "TraceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

[TraceId](#)

The trace request identifier. This is generated by IoT managed integrations and can be used to trace this command and its related operations in CloudWatch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9:=-_]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartAccountAssociationRefresh

Initiates a refresh of an existing account association to update its authorization and connection status.

Request Syntax

```
POST /account-associations/AccountAssociationId/refresh HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountAssociationId

The unique identifier of the account association to refresh.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "OAuthAuthorizationUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OAuthAuthorizationUrl

Third-party IoT platform OAuth authorization server URL with all required parameters to perform end-user authentication during the refresh process. This field will be empty when using General Authorization flows that do not require OAuth.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `$|^(https):\\/.*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartDeviceDiscovery

This API is used to start device discovery for hub-connected and third-party-connected devices. The authentication material (install code) is delivered as a message to the controller instructing it to start the discovery.

Request Syntax

POST /device-discoveries HTTP/1.1

Content-type: application/json

```
{
  "AccountAssociationId": "string",
  "AuthenticationMaterial": "string",
  "AuthenticationMaterialType": "string",
  "ClientToken": "string",
  "ConnectorAssociationIdentifier": "string",
  "ConnectorDeviceIdList": [ "string" ],
  "ControllerIdentifier": "string",
  "CustomProtocolDetail": {
    "string" : "string"
  },
  "DiscoveryType": "string",
  "EndDeviceIdentifier": "string",
  "Protocol": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountAssociationId

The identifier of the cloud-to-cloud account association to use for discovery of third-party devices.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

AuthenticationMaterial

The authentication material required to start the local device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9A-Za-z_\\-\\+=\\/:;]+

Required: No

AuthenticationMaterialType

The type of authentication material used for device discovery jobs.

Type: String

Valid Values: ZWAVE_INSTALL_CODE

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

ConnectorAssociationIdentifier

This parameter has been deprecated.

The id of the connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

ConnectorDeviceIdList

Used as a filter for PLA discoveries.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

ControllerIdentifier

The id of the end-user's IoT hub.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

CustomProtocolDetail

Additional protocol-specific details required for device discovery, which vary based on the discovery type.

Note

For a `DiscoveryType` of `CUSTOM`, the string-to-string map must have a key value of `Name` set to a non-empty-string.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: [a-zA-Z0-9 _.-]+

Value Length Constraints: Minimum length of 1. Maximum length of 512.

Value Pattern: [a-zA-Z0-9 _.{ }:"'-]+

Required: No

DiscoveryType

The discovery type supporting the type of device to be discovered in the device discovery task request.

Type: String

Valid Values: ZWAVE | ZIGBEE | CLOUD | CUSTOM |
CONTROLLER_CAPABILITY_REDISCOVERY

Required: Yes

EndDeviceIdentifier

The unique id of the end device for capability rediscovery.

Note

This parameter is only available when the discovery type is
CONTROLLER_CAPABILITY_REDISCOVERY.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

Protocol

The protocol type for capability rediscovery (ZWAVE, ZIGBEE, or CUSTOM).

Note

This parameter is only available when the discovery type is CONTROLLER_CAPABILITY_REDISCOVERY.

Type: String

Valid Values: ZWAVE | ZIGBEE | CUSTOM

Required: No

Tags

This parameter has been deprecated.

A set of key/value pairs that are used to manage the device discovery request.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "Id": "string",
  "StartedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The id of the device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

StartedAt

The timestamp value for the start time of the device discovery.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds tags to a specified resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource to which to add tags.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:(managed-thing|provisioning-profile|ota-task|credential-locker|account-association)/[0-9a-zA-Z-]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Tags](#)

A set of key/value pairs that are used to manage the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InvalidRequestException

The request is not valid.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a specified resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource from which to remove tags.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:(managed-thing|provisioning-profile|ota-task|credential-locker|account-association)/[0-9a-zA-Z-]+`

Required: Yes

TagKeys

A list of tag keys to remove from the resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InvalidRequestException

The request is not valid.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateAccountAssociation

Updates the properties of an existing account association.

Request Syntax

```
PUT /account-associations/AccountAssociationId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

AccountAssociationId

The unique identifier of the account association to update.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The new description to assign to the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9- _ ]+`

Required: No

Name

The new name to assign to the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateCloudConnector

Update an existing cloud connector.

Request Syntax

```
PUT /cloud-connectors/Identifier HTTP/1.1
Content-type: application/json
```

```
{
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The unique identifier of the cloud connector to update.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The new description to assign to the cloud connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Name

The new display name to assign to the cloud connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateConnectorDestination

Updates the properties of an existing connector destination.

Request Syntax

PUT /connector-destinations/*Identifier* HTTP/1.1

Content-type: application/json

```
{
  "AuthConfig": {
    "GeneralAuthorizationUpdate": {
      "AuthMaterialsToAdd": [
        {
          "AuthMaterialName": "string",
          "SecretsManager": {
            "arn": "string",
            "versionId": "string"
          }
        }
      ],
      "AuthMaterialsToUpdate": [
        {
          "AuthMaterialName": "string",
          "SecretsManager": {
            "arn": "string",
            "versionId": "string"
          }
        }
      ]
    },
    "oAuthUpdate": {
      "oAuthCompleteRedirectUrl": "string",
      "proactiveRefreshTokenRenewal": {
        "DaysBeforeRenewal": number,
        "enabled": boolean
      }
    }
  },
  "AuthType": "string",
  "Description": "string",
  "Name": "string",
  "SecretsManager": {
```

```
  "arn": "string",  
  "versionId": "string"  
}  
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The unique identifier of the connector destination to update.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

AuthConfig

The updated authentication configuration details for the connector destination.

Type: [AuthConfigUpdate](#) object

Required: No

AuthType

The new authentication type to use for the connector destination.

Type: String

Valid Values: OAUTH

Required: No

Description

The new description to assign to the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Required: No

Name

The new display name to assign to the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

SecretsManager

The updated AWS Secrets Manager configuration for the connector destination.

Type: [SecretsManager](#) object

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

UpdateDestination

Update a destination specified by name.

Request Syntax

```
PUT /destinations/Name HTTP/1.1
Content-type: application/json

{
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "RoleArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Name

The name of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+`

Required: No

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: No

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\ ]+`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 201
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateEventLogConfiguration

Update an event log configuration by log configuration ID.

Request Syntax

```
PATCH /event-log-configurations/Id HTTP/1.1
Content-type: application/json

{
  "EventLogLevel": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Id

The log configuration id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

EventLogLevel

The log level for the event in terms of severity.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateManagedThing

Update the attributes and capabilities associated with a managed thing.

Request Syntax

```
PUT /managed-things/Identifier HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Brand": "string",
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
            "id": "string",
            "name": "string",
            "properties": [ "string" ],
            "version": "string"
          }
        ],
        "deviceTypes": [ "string" ],
        "id": "string"
      }
    ],
    "nodeId": "string",
    "version": "string"
  },
  "CapabilitySchemas": [
    {
      "CapabilityId": "string",
      "ExtrinsicId": "string",
      "ExtrinsicVersion": number,
      "Format": "string",
      "Schema": JSON value
    }
  ],
  "Classification": "string",
  "CredentialLockerId": "string",
```

```
"HubNetworkMode": "string",
"MetaData": {
  "string" : "string"
},
"Model": "string",
"Name": "string",
"Owner": "string",
"SerialNumber": "string",
"WiFiSimpleSetupConfiguration": {
  "EnableAsProvisionee": boolean,
  "EnableAsProvisioner": boolean,
  "TimeoutInMinutes": number
}
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Capabilities

This parameter has been deprecated.

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { \$ } \ [\] = _ \ - \ +] +

Required: No

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

Required: No

CapabilitySchemas

The updated capability schemas that define the functionality and features supported by the managed thing.

Type: Array of [CapabilitySchemaItem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

CredentialLockerId

The identifier of the credential for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: No

HubNetworkMode

The network mode for the hub-connected device.

Type: String

Valid Values: STANDARD | NETWORK_WIDE_EXCLUSION

Required: No

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: `.*[a-zA-Z0-9_.,@/:#-]+.*`

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: `.*[a-zA-Z0-9_.,@/:#-]*.*`

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@- ]+`

Required: No

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Required: No

WiFiSimpleSetupConfiguration

The Wi-Fi Simple Setup configuration for the managed thing, which defines provisioning capabilities and timeout settings.

Type: [WiFiSimpleSetupConfiguration](#) object

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateNotificationConfiguration

Update a notification configuration.

Request Syntax

```
PUT /notification-configurations/EventType HTTP/1.1
Content-type: application/json
```

```
{
  "DestinationName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

EventType

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request accepts the following data in JSON format.

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._- ]+`

Required: Yes

Response Syntax

```
HTTP/1.1 201
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateOtaTask

Update an over-the-air (OTA) task.

Request Syntax

```
PUT /ota-tasks/Identifier HTTP/1.1
Content-type: application/json
```

```
{
  "Description": "string",
  "TaskConfigurationId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Managed integrations for AWS IoT Device Management API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AbortConfigCriteria](#)
- [AccountAssociationItem](#)
- [AuthConfig](#)
- [AuthConfigUpdate](#)
- [AuthMaterial](#)
- [CapabilityAction](#)
- [CapabilityReport](#)
- [CapabilityReportCapability](#)
- [CapabilityReportEndpoint](#)
- [CapabilitySchemaItem](#)
- [CommandCapability](#)
- [CommandEndpoint](#)
- [ConfigurationError](#)
- [ConfigurationStatus](#)
- [ConnectorDestinationSummary](#)
- [ConnectorItem](#)
- [CredentialLockerSummary](#)
- [DestinationSummary](#)
- [Device](#)
- [DeviceDiscoverySummary](#)

- [DiscoveredDeviceSummary](#)
- [EndpointConfig](#)
- [EventLogConfigurationSummary](#)
- [ExponentialRolloutRate](#)
- [GeneralAuthorizationName](#)
- [GeneralAuthorizationUpdate](#)
- [LambdaConfig](#)
- [ManagedThingAssociation](#)
- [ManagedThingSchemaListItem](#)
- [ManagedThingSummary](#)
- [MatterCapabilityReport](#)
- [MatterCapabilityReportAttribute](#)
- [MatterCapabilityReportCluster](#)
- [MatterCapabilityReportEndpoint](#)
- [MatterCluster](#)
- [MatterEndpoint](#)
- [NotificationConfigurationSummary](#)
- [OAuthConfig](#)
- [OAuthUpdate](#)
- [OtaTaskAbortConfig](#)
- [OtaTaskConfigurationSummary](#)
- [OtaTaskExecutionRetryConfig](#)
- [OtaTaskExecutionRolloutConfig](#)
- [OtaTaskExecutionSummaries](#)
- [OtaTaskExecutionSummary](#)
- [OtaTaskSchedulingConfig](#)
- [OtaTaskSummary](#)
- [OtaTaskTimeoutConfig](#)
- [ProactiveRefreshTokenRenewal](#)
- [ProvisioningProfileSummary](#)

- [PushConfig](#)
- [RetryConfigCriteria](#)
- [RolloutRateIncreaseCriteria](#)
- [RuntimeLogConfigurations](#)
- [ScheduleMaintenanceWindow](#)
- [SchemaVersionListItem](#)
- [SecretsManager](#)
- [StateCapability](#)
- [StateEndpoint](#)
- [TaskProcessingDetails](#)
- [WiFiSimpleSetupConfiguration](#)

AbortConfigCriteria

Structure representing one abort config criteria.

Contents

Action

The action taken by the abort configuration.

Type: String

Valid Values: CANCEL

Required: No

FailureType

Over-the-air (OTA) task abort criteria failure type.

Type: String

Valid Values: FAILED | REJECTED | TIMED_OUT | ALL

Required: No

MinNumberOfExecutedThings

The minimum number of things that must receive task execution notifications before the task can be aborted.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

ThresholdPercentage

The minimum percentage of over-the-air (OTA) task execution failures that must occur to initiate the last abort.

Type: Double

Valid Range: Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountAssociationItem

Structure containing information about an account association, including its identifier, state, and related metadata.

Contents

AccountAssociationId

The unique identifier of the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

AssociationState

The current state of the account association, indicating its status in the association lifecycle.

Type: String

Valid Values: `ASSOCIATION_IN_PROGRESS` | `ASSOCIATION_FAILED` | `ASSOCIATION_SUCCEEDED` | `ASSOCIATION_DELETING` | `REFRESH_TOKEN_EXPIRED`

Required: Yes

Arn

The Amazon Resource Name (ARN) of the account association.

Type: String

Length Constraints: Minimum length of 67. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:account-association/[0-9a-zA-Z-]+`

Required: No

ConnectorDestinationId

The identifier of the connector destination associated with this account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

Description

A description of the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9- _]+

Required: No

ErrorMessage

The error message explaining any issues with the account association, if applicable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9- _]+

Required: No

Name

The name of the account association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthConfig

The authentication configuration details for a connector destination, including OAuth settings and other authentication parameters.

Contents

GeneralAuthorization

The authorization materials for General Authorization.

Type: Array of [AuthMaterial](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

oAuth

The OAuth configuration settings used for authentication with the third-party service.

Type: [OAuthConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthConfigUpdate

The updated authentication configuration details for a connector destination.

Contents

GeneralAuthorizationUpdate

The General Authorization update information containing authorization materials to add or update.

Type: [GeneralAuthorizationUpdate](#) object

Required: No

OAuthUpdate

The updated OAuth configuration settings for the authentication configuration.

Type: [OAuthUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthMaterial

The authorization material containing the Secrets Manager arn and version.

Contents

AuthMaterialName

The name of the authorization material.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9=_+/-]+

Required: Yes

SecretsManager

Configuration for AWS Secrets Manager, used to securely store and manage sensitive information for connector destinations.

Type: [SecretsManager](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityAction

Action for an AWS capability, containing the action parameters for control.

Contents

name

Describe a capability action with a name.

Type: String

Pattern: [/a-zA-Z]+

Required: Yes

actionTraceId

Describe a capability action with an actionTraceId for a response command.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 20.

Pattern: [a-zA-Z0-9]+(?:_[0-9]+)?

Required: No

parameters

Describe a capability action with a capability property.

Type: JSON value

Required: No

ref

Describe a capability action with an reference.

Type: String

Pattern: [a-zA-Z.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReport

Report of all capabilities supported by the device.

Contents

endpoints

The endpoints used in the capability report.

Type: Array of [CapabilityReportEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: Yes

version

The version of the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: 1\.\0\.\0

Required: Yes

nodeId

The numeric identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_.,@+\-\/]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReportCapability

The capability used in capability report.

Contents

actions

The capability actions used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: Yes

events

The capability events used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: Yes

id

The id of the schema version.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?|\$latest)`

Required: Yes

name

The name of the capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [/a-zA-Z0-9\._ -]+

Required: Yes

properties

The capability properties used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [/a-zA-Z0-9\._ -]+

Required: Yes

version

The version of the capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: (0|[1-9][0-9]*)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReportEndpoint

The endpoint used in the capability report.

Contents

capabilities

The capabilities used in the capability report.

Type: Array of [CapabilityReportCapability](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: Yes

deviceTypes

The type of device.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[a-zA-Z0-9=_.,@+\\-/+]`

Required: Yes

id

The id of the endpoint used in the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilitySchemaItem

Structure representing a capability schema item that defines the functionality and features supported by a managed thing.

Contents

CapabilityId

The unique identifier of the capability defined in the schema.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?)|\\$latest)`

Required: Yes

ExtrinsicId

The external identifier for the capability, used when referencing the capability outside of the AWS ecosystem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: Yes

ExtrinsicVersion

The version of the external capability definition, used to track compatibility with external systems.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: Yes

Format

The format of the capability schema, which defines how the schema is structured and interpreted.

Type: String

Valid Values: AWS | ZCL | CONNECTOR

Required: Yes

Schema

The actual schema definition that describes the capability's properties, actions, and events.

Type: JSON value

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandCapability

The command capabilities added for the managed thing

Contents

actions

Describe the command capability with the actions it supports.

Type: Array of [CapabilityAction](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

id

Describe the capability with an id.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?|\$latest)`

Required: Yes

name

Describe the capability with an name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: Yes

version

Describe the capability with a version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: (`0` | `[1-9][0-9]*`)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandEndpoint

The endpoint for a managed thing when sending a command.

Contents

capabilities

Describe the endpoint with an id, a name, and the relevant capabilities for sending commands.

Type: Array of [CommandCapability](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

endpointId

The id of the endpoint for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConfigurationError

Provides the default encryption configuration error update details.

Contents

code

The error code returned when the default encryption configuration update fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

message

The error message returned when the default encryption configuration update fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\-. _ ,]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConfigurationStatus

Provides the status of the default encryption configuration for an AWS account.

Contents

state

The status state describing the default encryption configuration update.

Type: String

Valid Values: ENABLED | UPDATE_IN_PROGRESS | UPDATE_FAILED

Required: Yes

error

The error details describing a failed default encryption configuration update.

Type: [ConfigurationError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectorDestinationSummary

Structure containing summary information about a connector destination, which defines how a cloud-to-cloud connector connects to a customer's AWS account.

Contents

CloudConnectorId

The identifier of the cloud connector associated with this connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

Description

A description of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Id

The unique identifier of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

Name

The display name of the connector destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectorItem

Structure describing a connector.

Contents

EndpointConfig

The configuration details for the cloud connector endpoint, including connection parameters and authentication requirements.

Type: [EndpointConfig](#) object

Required: Yes

Name

The display name of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: Yes

Description

A description of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Required: No

EndpointType

The type of endpoint used for the C2C connector.

Type: String

Valid Values: LAMBDA

Required: No

Id

The identifier of the C2C connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

Type

The type of cloud connector created.

Type: String

Valid Values: LISTED | UNLISTED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CredentialLockerSummary

Structure describing one Credential Locker.

Contents

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

Required: No

CreatedAt

The timestamp value of when the credential locker was created at.

Type: Timestamp

Required: No

Id

The id of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: No

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DestinationSummary

Structure describing a destination for IoT managed integrations to deliver notifications for a device.

Contents

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+`

Required: No

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: No

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\ ]+`

Required: No

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the delivery destination.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Device

Describe the device using the relevant metadata and supported clusters for device discovery.

Contents

CapabilityReport

The capability report for the device.

Type: [MatterCapabilityReport](#) object

Required: Yes

ConnectorDeviceId

The device id as defined by the connector.

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

Required: Yes

CapabilitySchemas

Report of all capabilities supported by the device.

Type: Array of [CapabilitySchemaItem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: No

ConnectorDeviceName

The name of the device as defined by the connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: No

DeviceMetadata

The metadata attributes for a device.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceDiscoverySummary

Structure containing summary information about a device discovery job, including its identifier, type, and status.

Contents

DiscoveryType

The type of discovery process used to find devices.

Type: String

Valid Values: ZWAVE | ZIGBEE | CLOUD | CUSTOM | CONTROLLER_CAPABILITY_REDISCOVERY

Required: No

Id

The unique identifier of the device discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: No

Status

The current status of the device discovery job.

Type: String

Valid Values: RUNNING | SUCCEEDED | FAILED | TIMED_OUT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DiscoveredDeviceSummary

Structure containing summary information about a device discovered during a device discovery job.

Contents

AuthenticationMaterial

The authentication material required for connecting to the discovered device, such as credentials or tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[0-9A-Za-z!#$%&()*\+\-;<=>?@^_`{|}~\/: {} , \\""]+`

Required: No

Brand

The brand of the discovered device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_ ]+`

Required: No

ConnectorDeviceId

The third-party device identifier as defined by the connector. This identifier must not contain personal identifiable information (PII).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.,@- ]+`

Required: No

ConnectorDeviceName

The name of the device as defined by the connector or third-party system.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\p{L}\p{N} ._-]+`

Required: No

DeviceTypes

The list of device types or categories that the discovered device belongs to.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[a-zA-Z0-9=_.,@+\-/+]`

Required: No

DiscoveredAt

The timestamp indicating when the device was discovered.

Type: Timestamp

Required: No

ManagedThingId

The identifier of the managed thing created for this discovered device, if one exists.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: No

Model

The model of the discovered device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Modification

The status of the discovered device, indicating whether it has been added, removed, or modified since the last discovery.

Type: String

Valid Values: DISCOVERED | UPDATED | NO_CHANGE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EndpointConfig

The configuration details for an endpoint, which defines how to connect to and communicate with external services.

Contents

lambda

The Lambda function configuration for the endpoint, used when the endpoint communicates through an AWS Lambda function.

Type: [LambdaConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventLogConfigurationSummary

List of event log configurations.

Contents

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

Id

The identifier of the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: No

ResourceId

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

Required: No

ResourceType

The type of resource for the event log configuration.

Type: String

Pattern: `[*]$|^(managed-thing|credential-locker|provisioning-profile|ota-task|account-association)`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExponentialRolloutRate

Structure representing exponential rate of rollout for an over-the-air (OTA) task.

Contents

BaseRatePerMinute

The base rate per minute for the rollout of an over-the-air (OTA) task.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

IncrementFactor

The incremental factor for increasing the rollout rate of an over-the-air (OTA) task.

Type: Double

Valid Range: Minimum value of 1.1. Maximum value of 5.

Required: No

RateIncreaseCriteria

The criteria for increasing the rollout rate of an over-the-air (OTA) task.

Type: [RolloutRateIncreaseCriteria](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GeneralAuthorizationName

The General Authorization reference by authorization material name.

Contents

AuthMaterialName

The name of the authorization material.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9=_+/-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GeneralAuthorizationUpdate

The General Authorization update information containing authorization materials to add or update.

Contents

AuthMaterialsToAdd

The authorization materials to add.

Type: Array of [AuthMaterial](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

AuthMaterialsToUpdate

The authorization materials to update.

Type: Array of [AuthMaterial](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LambdaConfig

Configuration details for an AWS Lambda function used as an endpoint for a cloud connector.

Contents

arn

The Amazon Resource Name (ARN) of the Lambda function used as an endpoint.

Type: String

Pattern: (arn:aws:lambda:[0-9a-zA-Z-]+:[0-9]+:function:)?([a-zA-Z0-9-_]+(:(\\$LATEST|[a-zA-Z0-9-_]+))?)?)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedThingAssociation

Structure representing an association between a managed thing and an account association, which connects a device to a third-party account.

Contents

AccountAssociationId

The identifier of the account association in the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: No

ManagedThingAssociationStatus

The status of the registration between the managed thing and the account association. Indicates whether the device is pre-associated or fully associated with the account association.

Type: String

Valid Values: `PRE_ASSOCIATED` | `ASSOCIATED`

Required: No

ManagedThingId

The identifier of the managed thing in the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedThingSchemaListItem

Structure representing one schema item associated with a managed thing.

Contents

CapabilityId

The id of the capability for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9./]+(@\d+\\.\\d+)?`

Required: No

EndpointId

The id of the endpoint for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: No

Schema

The validation schema for one schema item associated with a managed thing.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedThingSummary

Structure representing one managed thing.

Contents

ActivatedAt

The timestamp value of when the managed thing was activated at.

Type: Timestamp

Required: No

AdvertisedProductId

The id of the advertised product.

Type: String

Length Constraints: Fixed length of 5.

Pattern: ([A-Za-z0-9!#\$%&()*\+\-;=>?@^_`{|}~])+

Required: No

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+

Required: No

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

ConnectorDestinationId

The identifier of the connector destination associated with this managed thing, if applicable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

ConnectorDeviceId

The third-party device id as defined by the connector. This device id must not contain personal identifiable information (PII).

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_ . , @-]+

Required: No

ConnectorPolicyId

This member has been deprecated.

The id of the connector policy.

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

Required: No

CredentialLockerId

The identifier of the credential locker for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Id

The id of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\p{L}\p{N} ._-]+

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

ParentControllerId

Id of the controller device used for the discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9]+

Required: No

ProvisioningStatus

The provisioning status of the device in the provisioning workflow for onboarding to IoT managed integrations. For more information, see [Device Provisioning](#).

Type: String

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED | DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

Required: No

Role

The type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

Required: No

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

UpdatedAt

The timestamp value of when the managed thing was last updated at.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterCapabilityReport

Matter based capability report.

Contents

endpoints

The endpoints used in the capability report.

Type: Array of [MatterCapabilityReportEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

version

The version of the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: 1\.\0\.\0

Required: Yes

nodeId

The numeric identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_.,@+\-\/]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterCapabilityReportAttribute

Matter attribute used in capability report.

Contents

id

The id of the Matter attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: No

name

Name for the AWS Matter capability report attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: No

value

Value for the AWS Matter capability report attribute.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterCapabilityReportCluster

Capability used in Matter capability report.

Contents

id

The id of the AWS Matter capability report cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: Yes

revision

The id of the revision for the AWS Matter capability report.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: Yes

attributes

The attributes of the AWS Matter capability report.

Type: Array of [MatterCapabilityReportAttribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

commands

The commands used with the AWS Matter capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `^[0-9a-fA-F]+$`

Required: No

events

The events used with the AWS Matter capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `^[0-9a-fA-F]+$`

Required: No

fabricIndex

The fabric index for the AWS Matter capability report.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 4096.

Required: No

featureMap

32 bit-map used to indicate which features a cluster supports.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 4294967295.

Required: No

generatedCommands

Matter clusters used in capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: No

name

The capability name used in the AWS Matter capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: No

publicId

The id of the schema version.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?|\$latest)`

Required: No

specVersion

The spec version used in the AWS Matter capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `\d+\.\d+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterCapabilityReportEndpoint

Matter endpoint used in capability report.

Contents

clusters

Matter clusters used in capability report.

Type: Array of [MatterCapabilityReportCluster](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

deviceTypes

The type of device.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [a-zA-Z0-9=_.,@+\\-/+]

Required: Yes

id

The id of the AWS Matter capability report endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: Yes

clientClusters

Semantic information related to endpoint.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 32 items.

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: No

parts

Heirachy of child endpoints contained in the given endpoint.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 32 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: No

semanticTags

Semantic information related to endpoint.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 32 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[0-9a-zA-Z._-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterCluster

Describe a Matter cluster with an id, and the relevant attributes, commands, and events.

Contents

attributes

The Matter attributes.

Type: JSON value

Required: No

commands

Describe the Matter commands with the Matter command identifier mapped to the command fields.

Type: String to JSON value map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 24.

Key Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: No

events

Describe the Matter events with the Matter event identifier mapped to the event fields.

Type: String to JSON value map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 24.

Key Pattern: `0[xX][0-9a-fA-F]+$|^[0-9]+`

Required: No

id

The cluster id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 24.

Pattern: `^[xX][0-9a-fA-F]+$|^[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatterEndpoint

Structure describing a managed thing.

Contents

clusters

A list of Matter clusters for a managed thing.

Type: Array of [MatterCluster](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

id

The Matter endpoint id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotificationConfigurationSummary

Structure describing a notification configuration.

Contents

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _ - ]+`

Required: No

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: `DEVICE_COMMAND | DEVICE_COMMAND_REQUEST |
DEVICE_DISCOVERY_STATUS | DEVICE_EVENT | DEVICE_LIFE_CYCLE |
DEVICE_STATE | DEVICE_OTA | DEVICE_WSS | CONNECTOR_ASSOCIATION |
ACCOUNT_ASSOCIATION | CONNECTOR_ERROR_REPORT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OAuthConfig

Configuration details for OAuth authentication with a third-party service.

Contents

authUrl

The authorization URL for the OAuth service, where users are directed to authenticate and authorize access.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `https?:\:\/\/(www\.)?[-a-zA-Z0-9@:%._\+~#=]{1,256}\.[a-zA-Z0-9()]{1,6}([-a-zA-Z0-9()@:%._\+~#?&\/=]*)`

Required: Yes

tokenEndpointAuthenticationScheme

The authentication scheme used when requesting tokens from the token endpoint.

Type: String

Valid Values: HTTP_BASIC | REQUEST_BODY_CREDENTIALS

Required: Yes

tokenUrl

The token URL for the OAuth service, where authorization codes are exchanged for access tokens.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `https?:\:\/\/(www\.)?[-a-zA-Z0-9@:%._\+~#=]{1,256}\.[a-zA-Z0-9()]{1,6}([-a-zA-Z0-9()@:%._\+~#?&\/=]*)`

Required: Yes

oAuthCompleteRedirectUrl

The URL where users are redirected after completing the OAuth authorization process.

Type: String

Required: No

proactiveRefreshTokenRenewal

Configuration for proactively refreshing OAuth tokens before they expire.

Type: [ProactiveRefreshTokenRenewal](#) object

Required: No

scope

The OAuth scopes requested during authorization, which define the permissions granted to the application.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OAuthUpdate

Structure containing updated OAuth configuration settings.

Contents

oAuthCompleteRedirectUrl

The updated URL where users are redirected after completing the OAuth authorization process.

Type: String

Required: No

proactiveRefreshTokenRenewal

Updated configuration for proactively refreshing OAuth tokens before they expire.

Type: [ProactiveRefreshTokenRenewal](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskAbortConfig

Over-the-air (OTA) task abort config.

Contents

AbortConfigCriteriaList

The list of criteria for the abort config.

Type: Array of [AbortConfigCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskConfigurationSummary

Structure representing one over-the-air (OTA) task configuration.

Contents

CreatedAt

The timestamp value of when the over-the-air (OTA) task configuration was created at.

Type: Timestamp

Required: No

Name

The name of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

TaskConfigurationId

The id of the over-the-air (OTA) task configuration

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Contents

RetryConfigCriteria

The list of retry config criteria.

Type: Array of [RetryConfigCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionRolloutConfig

Over-the-air (OTA) task rollout config.

Contents

ExponentialRolloutRate

Structure representing exponential rate of rollout for an over-the-air (OTA) task.

Type: [ExponentialRolloutRate](#) object

Required: No

MaximumPerMinute

The maximum number of things that will be notified of a pending task, per minute.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionSummaries

Structure representing one execution summary.

Contents

ManagedThingId

The id of a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

TaskExecutionSummary

Structure representing one over-the-air (OTA) task execution summary

Type: [OtaTaskExecutionSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionSummary

Structure representing one over-the-air (OTA) task execution summary.

Contents

ExecutionNumber

The execution number of the over-the-air (OTA) task execution summary.

Type: Long

Required: No

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task execution summary was last updated.

Type: Timestamp

Required: No

QueuedAt

The timestamp value of when the over-the-air (OTA) task execution summary is targeted to start.

Type: Timestamp

Required: No

RetryAttempt

The number of retry attempts for starting the over-the-air (OTA) task execution summary after a failed attempt.

Type: Integer

Required: No

StartedAt

The timestamp value of when the over-the-air (OTA) task execution summary started.

Type: Timestamp

Required: No

Status

The status of the over-the-air (OTA) task execution summary.

Type: String

Valid Values: QUEUED | IN_PROGRESS | SUCCEEDED | FAILED | TIMED_OUT |
REJECTED | REMOVED | CANCELED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskSchedulingConfig

Over-the-air (OTA) task scheduling config.

Contents

EndBehavior

Specifies the end behavior for all task executions after a task reaches the selected `endTime`. If `endTime` is not selected when creating the task, then `endBehavior` does not apply.

Type: String

Valid Values: `STOP_ROLLOUT` | `CANCEL` | `FORCE_CANCEL`

Required: No

EndTime

The time an over-the-air (OTA) task will stop.

Type: String

Required: No

MaintenanceWindows

Maintenance window list for over-the-air (OTA) task scheduling config.

Type: Array of [ScheduleMaintenanceWindow](#) objects

Required: No

StartTime

The time an over-the-air (OTA) task will start.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskSummary

Structure representing one over-the-air (OTA) task.

Contents

CreatedAt

The timestamp value of when the over-the-air (OTA) task was created at.

Type: Timestamp

Required: No

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task was last updated at.

Type: Timestamp

Required: No

Status

The status of the over-the-air (OTA) task summary.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED | DELETION_IN_PROGRESS | SCHEDULED

Required: No

TaskArn

The Amazon Resource Name (ARN) of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/[0-9a-zA-Z-]+`

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: No

TaskId

The id of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `[A-Za-z0-9]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskTimeoutConfig

Over-the-air (OTA) task timeout config.

Contents

InProgressTimeoutInMinutes

Specifies the amount of time the device has to finish execution of this task. The timeout interval can be anywhere between 1 minute and 7 days.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 10080.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProactiveRefreshTokenRenewal

Configuration settings for proactively refreshing OAuth tokens before they expire.

Contents

DaysBeforeRenewal

The days before token expiration when the system should attempt to renew the token, specified in days.

Type: Integer

Valid Range: Minimum value of 30.

Required: No

enabled

Indicates whether proactive refresh token renewal is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProvisioningProfileSummary

Structure describing a provisioning profile.

Contents

Arn

The Amazon Resource Name (ARN) of the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

Required: No

Id

The identifier of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9-_]+`

Required: No

Name

The name of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[0-9A-Za-z_-]+`

Required: No

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Required: No

Status

The status of a provisioning profile.

Type: String

Valid Values: CREATE_IN_PROGRESS | CREATE_FAILED | CREATED |
DELETE_IN_PROGRESS | DELETE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PushConfig

Structure representing a push config.

Contents

AbortConfig

Structure representing one abort config.

Type: [OtaTaskAbortConfig](#) object

Required: No

RolloutConfig

Structure representing one rollout config.

Type: [OtaTaskExecutionRolloutConfig](#) object

Required: No

TimeoutConfig

Structure representing one timeout config.

Type: [OtaTaskTimeoutConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RetryConfigCriteria

Structure representing one retry config criteria.

Contents

FailureType

Over-the-air (OTA) retry criteria failure type.

Type: String

Valid Values: FAILED | TIMED_OUT | ALL

Required: No

MinNumberOfRetries

The number of retries allowed for a failure type for the over-the-air (OTA) task.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RolloutRateIncreaseCriteria

Structure representing rollout config criteria.

Contents

numberOfNotifiedThings

The threshold for number of notified things that will initiate the increase in rate of rollout.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

numberOfSucceededThings

The threshold for number of succeeded things that will initiate the increase in rate of rollout.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuntimeLogConfigurations

The different configurations for runtime logs.

Contents

DeleteLocalStoreAfterUpload

Configuration to enable or disable deleting of runtime logs in the device once uploaded to the cloud.

Type: Boolean

Required: No

LocalStoreFileRotationMaxBytes

Configuration to set the maximum bytes of runtime logs that can be stored on the device before the oldest logs are deleted or overwritten.

Type: Integer

Required: No

LocalStoreFileRotationMaxFiles

Configuration to set the maximum number of runtime log files that can be stored on the device before the oldest files are deleted or overwritten.

Type: Integer

Required: No

LocalStoreLocation

Configuration of where to store runtime logs in the device.

Type: String

Required: No

LogFlushLevel

The different log levels available for configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

LogLevel

The different log levels available for configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

UploadLog

Configuration to enable or disable uploading of runtime logs to the cloud.

Type: Boolean

Required: No

UploadPeriodMinutes

Configuration to set the time interval in minutes between each batch of runtime logs that the device uploads to the cloud.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleMaintenanceWindow

Structure representing scheduling maintenance window.

Contents

DurationInMinutes

Displays the duration of the next maintenance window.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1430.

Required: No

StartTime

Displays the start time of the next maintenance window.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaVersionListItem

List item describing a schema version.

Contents

Description

A description of the schema version.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: [a-zA-Z0-9.,/ -]+

Required: No

Namespace

The name of the schema version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: [a-z0-9]+

Required: No

Schemald

The identifier of the schema version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: [a-zA-Z0-9.]+

Required: No

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 12.

Pattern: (`\d+\.\d+(\.\d+)?|\$latest`)

Required: No

Type

The type of schema version.

Type: String

Valid Values: `capability` | `definition`

Required: No

Visibility

The visibility of the schema version.

Type: String

Valid Values: `PUBLIC` | `PRIVATE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecretsManager

Configuration for AWS Secrets Manager, used to securely store and manage sensitive information for connector destinations.

Contents

arn

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:secretsmanager:[0-9a-zA-Z-]{1,32}:\d{12}:secret:[A-Za-z0-9/_+=.@-]{8,520}`

Required: Yes

versionId

The version ID of the AWS Secrets Manager secret.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `[a-zA-Z0-9-_]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateCapability

State capabilities added for the managed thing.

Contents

id

The id of the managed thing in the capability report.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 128.

Pattern: `[a-zA-Z0-9.]+@(\d+\.\d+(\.\d+)?|\$latest)`

Required: Yes

name

Name for the AWS capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._ -]+`

Required: Yes

version

Version for the AWS capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `(0|[1-9][0-9]*)`

Required: Yes

properties

Describe the command capability with the properties it supports.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateEndpoint

Describe the endpoint with an Id, a name, and the relevant capabilities for reporting state

Contents

capabilities

Describe the endpoint with an id, a name, and the relevant capabilities for the reporting state.

Type: Array of [StateCapability](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

endpointId

Numeric identifier of the endpoint

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TaskProcessingDetails

Details about the over-the-air (OTA) task process.

Contents

NumberOfCanceledThings

The number of canceled things in an over-the-air (OTA) task.

Type: Integer

Required: No

NumberOfFailedThings

The number of failed things in an over-the-air (OTA) task.

Type: Integer

Required: No

NumberOfInProgressThings

The number of in progress things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfQueuedThings

The number of queued things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfRejectedThings

The number of rejected things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfRemovedThings

The number of removed things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfSucceededThings

The number of succeeded things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfTimedOutThings

The number of timed out things in an over-the-air (OTA) task.

Type: Integer

Required: No

processingTargets

The targets of the over-the-air (OTA) task.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WiFiSimpleSetupConfiguration

The Wi-Fi Simple Setup configuration for the managed thing, which defines provisioning capabilities and timeout settings.

Contents

EnableAsProvisionee

Indicates whether the device can act as a provisionee in Wi-Fi Simple Setup, allowing it to be configured by other devices.

Type: Boolean

Required: No

EnableAsProvisioner

Indicates whether the device can act as a provisioner in Wi-Fi Simple Setup, allowing it to configure other devices.

Type: Boolean

Required: No

TimeoutInMinutes

The timeout duration in minutes for Wi-Fi Simple Setup. Valid range is 5 to 15 minutes.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 15.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400